

RKSfluid®

A key Valve in Flow Control



- Streamlined, minimum noise
- Backflow velocity only 0.2s, Head loss 0.1bar with 2m/s
- EPDM/NBR Rubber fully coated disc
- Anti-erosion design, Self-adjusting ball
- Self-cleaning stem, Long time smooth operation

Engineering Projects



— RKSfluid —

- China standard reference unit, to participate in the development of the relevant valve industry standards.
- We have created a R&D and service center in Houston, Texas, USA.
- GB, German standard, American standard, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRAS WRC, KTW, API 6D, API 609



Our Factory



Partners



Company Advantages

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06



©

✓ CNC

✓

✓

✓ GB TUV CE ISO 9001 ADWO-2000 TS PED WRC
WRAS KTW API 6D API609

VI

Exhibition Photos





Q

A

Q□□□□□□□□□□□□□□□□
A□RKSfluid□□□□□□□□□□□□4□□□□□□□□□□□□

Q□MOQ.
A□□□□□□□1□□□

[illegible]

