

Product Description



Super Anti-corrosion
Epoxy powder coating **200-250µm**,
baking varnish over **200°C**,
use  material.



Free wedge nut, **reduces the stem bending forces** and at the same time enables it to be easily replaced.



The more compact new cap, reduces the water retention areas in order to **reduce the risk of bacterial growth**.



One piece stainless steel stem in for **better resistance to axial load and to with stand higher operating torques**.



Three locking tab for bayonet system prevents self-dismantling.



Dust guard integrating three O-ring shape, **prohibiting the introduction of foreign bodies** at the stem.



Male guiding system with composite sliding skate reduces the wear of the wedge against the body, allowing a smooth functionality and a longer life time of the valve.



Triple seal at the operating stem to ensure tightness with the test of time (2500 cycles).



New male composite sliding skate technology ensuring a low operating torque even under high differential pressure and preventing damage or corrosion generated by the friction.

Design standard

Design standard	BS EN 1171 ANSI
Flange	GB/T 17241.6-2008、 DIN 2633-1975、 BS EN1902-2
Face to face	GB/T 12221-2005、 ISO 5752-1988、 BS EN558-1(F4、 F5)
Test standard	EN12266

Specification

Size	DN50-900
Pressure	PN10 PN16 class150
Medium	Water
Temperature	0°C~90°C

PRODUCT DISPLAY



SHIPPING PACKAGING



COMPANY INFORMATION



©

✓ CNC

✓ 符合 ISO 9001 质量管理体系认证

✓ 符合 ISO 14001 环境管理体系认证

✓ 符合 GB 12224 标准，并符合 TUV CE、ISO 9001、ADWO-2000、TS、PED、WRC、WRAS、KTW、API 6D、API 609 等标准

VI 符合 CE 认证，并符合 PED 指令要求



A HRRRAULIC RKSfluid
□□□□□□

Q
A RKSfluid 4

Q
A 2~5

Q MOQ
A 1

Q
A 100 2
□□□ TUV □ API □ WRAS □ CE □ ISO □
□□□ DIN □ ASME □ BS EN □ JIS □ API □ AWWA □

Q
A RKSfluid 20 70