



Butterfly Valve

Ball Valve

Gate Valve

Globe Valve

Check Valve

Pipe Fittings

DESIGN FEATURES

VERSATILE & RANGE

- Up to 27mm of tolerance, DN40 ~ DN300 stock reduction
- Allows angular deflection of +/-5°
- Covering most common pipe materials



USER FRIENDLY

- Economical and applicable
- Easy Operation

OPTIMAL SEALING

- Unique gasket with circumferential ribs sealing on corroded, scored or pitted pipes

DURABLE

- Anti-corrosion
- Thickness: Epoxy powder coating of 200-250µm
- Temperature : Spraying temperature over 200 °C. Doesn't fade, even wipe with diethyl ether

MATERIAL

- Epoxy powder:  , Earth Best!
- Nuts: **DACROMET®** or **GEOMET®**, Earth Best!
- Cast iron: EN-GJS-500-7, nodularity over 95%!



APPLICATION SCENARIO



Industrial water application



Hydroelectric generation



Sewagetreatment



Water treatment



Water supply and drainage



Water transport



Pipe network in house



Irrigation



Our Factory



Company Advantages

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

02
4 factories

04
2 professional testing centers

05
High quality imported materials

06



I. Professional experience and technology

II. CNC processing center

III. Testing center

IV. Quality management system

V. Certifications: GB, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC, WRAS, KTW, API 6D, API 609

Exhibition Photos



Our Certificates



Q
A

Q
A

Q
A

Q
A

Q

A20150000000000000000000000000000

QMOQ

A100000000000

Q000000000000

A10000000000000000000000000000000

000TUVAPIWRASISO00000000

000DINASMEBS ENJISAPIAWWA00000000

Q000000000000000000000000000000

A0RKSfluid00000000000000000000000000000000