



## DESIGN FEATURES

### VERSATILE & RANGE

- Up to 28mm of tolerance, **DN40 ~ DN450** stock reduction
- Allows angular deflection of **+/-3°** per gasket
- Covering most common pipe materials



### OPTIMAL SEALING

- **Unique gasket** with circumferential ribs sealing on corroded, scored or pitted pipes

### DURABLE

- **ANTI-CORROSION**
- Thickness: **Epoxy powder** coating of **200-250µm**
- Temperature : Spraying temperature over **200°C**  
Doesn't fade, even wipe with **diethyl ether**

### MATERIAL

- Epoxy powder:  , Earth Best!
- Nuts: **DACROMET®** or **GEOMET®** , Earth Best!
- Cast iron: **EN-GJS-500-7**, nodularity over **95%**!
- Flange Adaptors: for most common flange standards. **PN10/16/ANSI150** drilled

### APPLICATION SCENARIO



# Our Factory



## Company Advantages

01

21 years of professional experience

03

Independent research and development team  
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06





I 工厂

II 工厂CNC

III 工厂

IV 工厂

V 工厂 GB 工厂 TUV CE ISO 9001 ADWO-2000 TS PED WRC WRAS KTW API 6D API 609

VI 工厂

## Exhibition Photos





A RKSfluid 20 70