



DESIGN FEATURES

VERSATILE & RANGE

- Up to 28mm of tolerance, **DN40 ~ DN450** stock reduction
- Allows angular deflection of **+/-3°** per gasket
- Covering most common pipe materials



OPTIMAL SEALING

- Unique gasket with circumferential ribs sealing on corroded, scored or pitted pipes

DURABLE

- ANTI-CORROSION
- Thickness: **Epoxy powder** coating of **200-250µm**
- Temperature : Spraying temperature over **200°C**
Doesn't fade, even wipe with **diethyl ether**

MATERIAL

- Epoxy powder: **AkzoNobel**, Earth Best!
- Nuts: **DACROMET®** or **GEOMET®**, Earth Best!
- Cast iron: **EN-GJS-500-7**, nodularity over **95%**!
- Flange Adaptors: for most common flange standards. **PN10/16/ANSI150** drilled



APPLICATION SCENARIO



Our Factory



Company Advantages

01 21 years of professional experience

03 Independent research and development team
28 top senior professional researchers

05 100% high level ex-factory inspection

07 2 years quality assurance, repair and replacement

02 4 factories

04 2 professional testing centers

06 High quality imported materials



I. 工厂概况

II. CNC加工中心及精密制造设备

III. 热销产品及解决方案

IV. 质量管理体系

V. 认证与标准：GB/T 19001-2008, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC, WRAS, KTW, API 6D, API 609

VI. 展会及客户案例展示

Exhibition Photos



Our Certificates



1

Q: RKSfluid

QGIS Fluid Tools

AIRKSfluid

QMOQ
A1

A|RKSfluid|20|00000000070|00000000000000000000000000000000