RKSfluid®
A key Valve in Flow Control
Butterfly Valve
Ball Valve
Gate Valve
Globe Valve
Check Valve
Pipe Fittings

Design Features

RANGE

- For DI, AC, PVC and Fibre cement pipes
- Dimension from **32-315mm**

DI Ductile Iron | **AC** Fibre Cement | **PVC** Poly Vinyl Chloride

LOW COST

- Structure compact and **convenient operation**

RELIABLE

- **EPDM gasket** to EN681-1
- **Anti-corrosive** coating
- Bichromated bolts on series 790

MATERIAL

- S700 & S750: Grey Cast Iron **EN-GJL-250** Quality
- S790: ductile iron **EN-GJS-400-15** Quality

Application Scenario

Our Factory

I□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

Ⅱ□□□CNC□□□

□□□□□□□□□□□□□□□□□□□□□□□Ⅲ□□□□□□□□□□□□

Ⅳ□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

V□□□□GB□□□□□□□□□□□□□□□□□TUV CE□ISO 9001□ADWO-2000□TS□PED□WRC WRAS□KTW□API 6D□API 609□

VI□□□/□□□/□□□□□□□□□□□□□□□□

Exhibition Photos
RKSfluid
RKSfluid®

Our Certificates
Real
Certificate
Zertifikat
WRAS
CERTIFICATE

□□□□□□

Q□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

A□□□□□□□□□□□□□□□□□□□□□□

Q□□□□□□□□□□□□□□□□□□□
A□□□□□□□□□□□□□□□□ RKSfluid□□□

Q□□□□□□□□□□
A□RKSfluid□□□□□□□□□□□□□4□□□□□□□□□□

Q□□□□□□□□□
A□□□□□□2□5□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

Q□MOQ
A□□□□□□1□□

Q□□□□□□□□□□□
A□□100□□□□□□□□2□□□□□□□□□□□□□□□□□□□□□□
□□□TUV□API□WRAS□□□□□ISO□□□□□□□□
□□□DIN□ASME□BS EN□JIS□API□AWWA□□□□□□□□

Q□□□□□□□□□□□□□□□□□□□□□□□□□
A□RKSfluid□20□□□□□□□□70□□□