

## Product Description



Super Anti-corrosion  
Epoxy powder coating **200-250µm**,  
baking varnish over **200°C**,  
use  material.



Free wedge nut, **reduces the stem bending forces** and at the same time enables it to be easily replaced.



The more compact new cap, reduces the water retention areas in order to **reduce the risk of bacterial growth**.



One piece stainless steel stem in for **better resistance to axial load and to with stand higher operating torques**.



**Three locking tab** for bayonet system prevents self-dismantling.



Dust guard integrating three O-ring shape, **prohibiting the introduction of foreign bodies** at the stem.



**Male guiding system with composite sliding skate** reduces the wear of the wedge against the body, allowing a smooth functionality and a longer life time of the valve.



**Triple seal at the operating stem** to ensure tightness with the test of time (2500 cycles).



**New male composite sliding skate technology** ensuring a low operating torque even under high differential pressure and preventing damage or corrosion generated by the friction.

## Design standard

Design standard	BS EN 1171 ANSI
Flange	GB/T 17241.6-2008、 DIN 2633-1975、 BS EN1902-2
Face to face	GB/T 12221-2005、 ISO 5752-1988、 BS EN558-1(F4、 F5)
Test standard	EN12266

## Specification

Size	DN50-900
Pressure	PN10 PN16 class150
Medium	Water
Temperature	0°C~90°C

# PRODUCT DISPLAY



# SHIPPING PACKAGING



# COMPANY INFORMATION



© 2023 RICKFLUID

✓ All CNC parts are precision-machined to meet the highest standards of quality and performance.

✓ 符合 ISO 9001 质量管理体系认证

✓ 符合 ISO 14001 环境管理体系认证

✓ 符合 GB 12224 标准，并符合 TUV CE、ISO 9001、ADWO-2000、TS、PED、WRC、WRAS、KTW、API 6D、API 609 等标准

VI 符合 CE 认证，并符合 PED 指令要求



## Exhibition Photos



## Our Certificates



□□□□□

Q□□□□□□□□□□□□□□□□□□□□□□□□

A□□□□□□□□□□□□□□□□□□□□□□□□

Q□□□□□□□□□□□□□□□□□□□□□□□□

A HRRRAULIC RKSfluid  
□□□□□□

Q  
A RKSfluid 4

Q  
A 2~5

Q MOQ  
A 1

Q  
A 100 2  
□□□ TUV □ API □ WRAS □ CE □ ISO □  
□□□ DIN □ ASME □ BS EN □ JIS □ API □ AWWA □

Q  
A RKSfluid 20 70