



RKSfluid®

A key Valve in Flow Control



Butterfly Valve



Ball Valve



Gate Valve



Globe Valve



Check Valve



Pipe Fittings

Introduction



Our Aluminum valve handwheel gearbox, 90 ° slewing drive device is suitable for butterfly valve, ball valve and plug valve and so on. The aluminum alloy material body after static electricity powder coating has an excellent appearance, strong adhesion/mechanical property and anti-corrosion/wear resistance.

Square: 8/ 9/ 11/ 14/ 17/ 19/ 22/ 27

ISO 5211 Flange Type: F05/ F07/ F09/ F10/ F12/ F14/ F16/ F25

Features



- ◆ ISO 5211 direct mount patterns.
- ◆ Filled with special lubricant before leaving the factory.
- ◆ Weatherproof is IP 65.
- ◆ The output torque range: 180-5500NM
- ◆ 5 degrees angle adjusting.
- ◆ All aluminum shell light and beautiful.

Application Scenario





APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



Our Factory



Company Advantages

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06



RKSfluid 1997 年 1 月 1 日 成立，公司总部位于中国山东省临沂市，拥有先进的 CNC 加工中心，专业生产各种精密零件，产品广泛应用于汽车、机械、农业等领域。公司通过了 GB 19001、ISO 9001、TS 16949、API 等认证，产品符合 GB、RKS、CE、ADWO-2000、TUV、ISO9001、TS、API 等标准。RKSfluid 1997 年 1 月 1 日 成立，公司总部位于中国山东省临沂市，拥有先进的 CNC 加工中心，专业生产各种精密零件，产品广泛应用于汽车、机械、农业等领域。公司通过了 GB 19001、ISO 9001、TS 16949、API 等认证，产品符合 GB、RKS、CE、ADWO-2000、TUV、ISO9001、TS、API 等标准。

I

II

III

IV

V GB TUV CE ISO 9001 ADWO-2000 TS PED WRC WRAS KTW API 6D API609

VI

Exhibition Photos



Our Certificates



□□□□□

Q□□□□□□□□□□□□□□□□□□□□□□□□

A□□□□□□□□□□□□□□□□□□□□□□□□

Q□□□□□□□□□□□□□□□

A□□□□□□□□□□□□ RKSfluid□□□□□□□□ USA□□□□□□□□□□□□□□□□□□□□□□□□

Q□□□□□□□□□□□□□□□□□

A□ RKSfluid□□□□□□□□□□□□□□□□□□□□□□□□

Q□□□□□□□□□□

A□□□□□□□□ 2□5□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

Q□□□□□□□□□□

A□□□□□□□□□□ 1□□

Q□□□□□□□□□□□□□

A□□□□□□ 100□□□□□□□□ 2□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

TUV□ API□ WRAS□ CE□ ISO□□□□□□□□□□□□

□□□□ DIN□ ASME□ BS EN□ JIS□ API□ AWWA□□□□□□□□□□□□

Q□□□□□□□□□□□□□□□□□□□□□□□□□□□

A RKSfluid 20 R&D