

## DESIGN FEATURES



### ● TECHNICAL REQUIREMENT

- 1.Design standard:BS 5163.
- 2.Face to face:BS 5163.
- 3.Flanges standard:BS EN1092-2:1997 PN16.
- 4.Test standard:BS EN12266-1 Rate B.

### ● FEATURES

- Double flange metal seated gate valve
- Size Range:DN50-DN2000
- Standard-ISO/BS/DIN/AWWA/API
- Tests Standard-BS EN 12266-1
- Body Ring-Bronze/SS420/SS304/SS316
- Body-Ductile Iron /Cast Iron/Stainless Steel /WCB
- Fusion bonded epoxy coating-min 300 microns



## RELATED PRODUCTS








**SMALL DIAMETER GATE VALVE**  
DN50-DN300,PN10/16/25



**METAL SEATED GATE VALVE**  
DN350-DN600,PN10/16/25



**LARGE DIAMETER  
METAL SEATED GATE VALVE**  
DN700-DN2000,PN10/16/25



I    □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □

II CNC

[illegible]

IV 符合所有适用的国家、地方、行业标准和规范

V 符合GB 15613-2008《危险废物焚烧污染控制标准》Tuv CE、ISO 9001、ADWO-200、TS、PED、WRC WRAS、KTW、API 6D、API609

符合所有适用的国家、地方、行业标准和规范/符合/符合所有适用的国家、地方、行业标准和规范



01

21 years of professional experience

03

Independent research and development team  
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06


## COMPANY QUALIFICATION



## COMPANY EXHIBITION



## Partners

|                                                                                   |                                                                                   |                                                                                    |                                                                                     |                                                                                     |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|  |  |  |  |  |
|  |  |  |  |  |
|  |  |  |  |  |



**Q:**

**A:**

```

#####
00: 000000000000000000000000000000000000 RKSfluid 000000000000000000000000000000000000

```

**Q:** 請問RKSfluid 4吋的規格?

答: RKSfluid 4吋的規格是符合API 600的規格

**D:** 請問

A: RKSfluid 2吋5吋的規格是符合API 600的規格

**D:** 請問

答: RKSfluid 1 吋

**Q:** 請問RKSfluid 4吋的規格?

答: RKSfluid 100% 符合API 600 2 吋的規格

Tuv API Wras CE ISO 9001 認證

符合DIN ASME BS EN JIS API Awwa 規格

**Q:** 請問RKSfluid 20 吋的規格?

A: RKSfluid 20 吋的規格是符合API 600 20 吋的規格