




## DESIGN FEATURES

### DURABLE

- No-pin connection, 1 pc blow-out proof stem
- DI/CI Nodularity over 95%

### ANTI-CORROSION

- Material: Epoxy powder:  , Earth Best!
- Coating Thickness: 200-250µm
- Spraying temp: over 200°C. Doesn't fade, even wipe with diethyl ether

### QUALITY STANDARD

- 100% quality test, follow DIN, ASTM, JIS, GB/T, ISO, BS EN, API
- ONLY ONE Manufacturer get CE certification up to DN1800
- 2 years warranty. 15000 times On-off test, 30000 times Destructive experiment





## APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport





## Company Advantages

01

21 years of professional experience

03

Independent research and development team  
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06



©

✓ CNC


✓

✓

✓ GB TUV CE ISO 9001 ADWO-2000 TS PED WRC WRAS KTW API 6D API609

VI

## Exhibition Photos



# Our Certificates



□□□□□

Q□□□□□□□□□□□□□□□□□□□□□□  
A□□□□□□□□□□□□□□□□□□□□□□□

Q□□□□□□□□□□□□□□□□□□□□□□□□  
A□□□□□□□□ HRAULIC □□□□□□□□□□ RKSfluid □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□  
□□□□□□□

Q□□□□□□□□□□□□□□□□□□□□□□□□  
A□ RKSfluid □□

Q□□□□□□□□□□  
A□□□□□□□□ 2~5 □□□

Q□□□□□□□□□□  
A□□□□□□□□□ 1□□□□

Q□□□□□□□□□□□□  
A□□□□□□□ 100 □□□□□□□□□□ 2 □□□  
□□□□ TUV □ API □ WRAS □ CE □ ISO □□□□□□□□□□  
□□□□ DIN □ ASME □ BS EN □ IS □ API □ AWWA □□

