



# RKSfluid®

A key Valve in Flow Control



Butterfly Valve



Ball Valve



Gate Valve



Globe Valve



Check Valve



Pipe Fittings



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: Ductile Iron+PTFE

Seat: PTFE

Connection: Wafer, Lug, Flange



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: Ductile Iron+PTFE

Seat: PTFE

Connection: Wafer, Lug, Flange



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB, CF8, CF8M

Disc: CF8+PTFE, CF8M+PTFE

Seat: PTFE

Connection: Wafer, Lug



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB, CF8, CF8M

Disc: CF8+PTFE, CF8M+PTFE

Seat: PTFE

Connection: Wafer, Lug



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: CF8, CF8M

Seat: PTFE

Connection: Wafer, Lug, Flange



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB

Disc: CF8 +PTFE, CF8 +PFA

Seat: PTFE

Connection: Wafer, Lug, Flange



Resilient seat butterfly valve



Resilient seat butterfly valve



Resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: DI+ Nylon

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange



Resilient seat butterfly valve



Double flange resilient seat butterfly valve



Short-neck butterfly valve for petroleum

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB, 5K/10K

Size:DN50-DN1000

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Flange

ANSI 125LB/150LB

Top Flange Standard:ISO5211

Size:2"-12"

Body: DI CI

Disc :Stainless Steel

Seat : EPDM, NBR, Viton

Connection:Wafer, Lug



## APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



# Our Factory



## Company Advantages

01

21 years of professional experience

03

Independent research and development team  
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06



RKSfluid 1997 年 成立。 公司 拥有  
 先进 设备， 采用 最新 技术 生产。 公司  
 CNC 加工 设备， 加工 精度 高， 交货 周期 短。  
 公司 拥有 完善 质量管理体系。 产品 符合  
 国际 标准。 公司 产品 广泛应用于 石油、 化工、  
 电力、 冶金、 船舶 等行业。 GB 标准 产品  
 符合 国际 标准。 公司拥有  
 完善 售后服务 体系。 RKS 公司  
 产品， 质量 可靠， 交货 及时。 公司 产品  
 符合 : GB, ISO, 符合 国际 标准, CE 符合 ADWO-2000 符合 TUV 符合  
 ISO9001, TS, API. 产品 符合 : 符合, 符合 国际 标准 符合 国际  
 标准 符合 国际 标准。 符合 国际, 符合 国际 标准。 符合 国际  
 标准 : 符合 国际, 符合, 符合, 符合 国际, 符合 国际 标准,  
 符合 国际。 符合 国际 标准 符合 国际 标准 符合 国际 标准。  
 "符合 国际 标准, 符合 国际 标准 符合 国际 标准" 符合 国际 标准  
 符合 国际 标准。 符合 国际 标准 符合 国际 标准!

I 符合 国际 : 符合 国际 标准, 符合 国际 标准 符合 国际 标准。

II 符合 CNC 符合 国际 标准, 符合 国际 标准, 符合 国际 标准, 符合 国际 标准 符合 国际 标准。

III 符合 国际 标准 符合 国际 标准 符合 国际 标准 符合 国际 标准 符合 国际 标准。

IV 符合 国际 标准 符合 国际 标准 符合 国际 标准 符合 国际 标准。

V 符合 国际 : GB, 符合 国际 标准, 符合 国际 标准, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609.

VI 符合 国际 标准 : 符合 国际 标准 符合 国际 标准, 符合 国际 标准, 符合 国际 标准, 符合 国际 标准, 符合 国际 标准, 符合 / 符合 / 符合 国际 标准, 符合 国际 标准。

## Exhibition Photos



## Our Certificates



Q : 100% 100% 100% 100% 100%?

A : 100%, 100%, 100%, 100%, 100% 100%.

Q : 100% 100% 100% 100%?

A : 100%, 100%, 100%, 100% 100%. RKSfluid 100% 100% 100%. 100% 100%, 100% 100%.

Q : 100% 100% 100%?

A : RKSfluid 100% 100% 100% 100% 4 100% 100% 100%.

Q : 100% 100%

: 100% 100% 2 ~ 5 %. 100% 100% 100%.

Q : MOQ

: 1 100% 100%.

Q : 100% 100% 100%?

: 100% 100% 100% 100% 2 100%. 100% 100% 100%.

100% TUV, API, WRAS, CE, ISO 100% 100%.

100% DIN, ASME, BS EN, JIS, API, AWWA 100%.

Q : 100% 100% 100% 100% 100%?

A : RKSfluid 20 100% 100% 100% 70 100% R & D 100% 100%, 100% 100% 100% 100%.