- Fireproof structural design, API607 / API6FA Standard
- Flexible sealing ring structure, reliable seating
- Safety locking device, error prevention
- Double block & bleed
- Anti-static design

Engineering Projects

Partners

PTFE lined butterfly valve

Resilient seat butterfly valve

Double offset butterfly valve

Triple offset butterfly valve

Ball valve

Pipe fittings

Our Factory

Company Advantages

01 21 years of professional experience

02 4 factories

03 Independent research and development team
28 top senior professional researchers

04 2 professional testing centers

05 100% high level ex-factory inspection

06 High quality imported materials

07 2 years quality assurance, repair and replacement

□□ □□ : □□ □□ □□, □□ □ □□□ □□.

II □□ CNC □□□ □□, □□ □□ □□, □□ □□, □□ □□ □□ □ □□.

III □□ □□ □□ □□, □□ □□ □□ □□□ □□□□ □□.

IV □□ □□□ □□□□ □□ □□ □□□ □□□□□□.

V □□ □□ : GB, □□ □□, □□ □□, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609.

□□, □□ □□ : □□ □□, □ □□, □□□ □□, □□ □□, □□□ □□, □□□ □□, □□ / □□ / □□ □□□□□, □□ □□□□.

Exhibition Photos

□□□□ □□

Q : □□□ □□□□ □□ □□□ □□□□□?
A : □□ □□, □□, □□, □□, □□, □□ □□□.

Q : □□□□□□ □□ □ □ □□□□? □ □□?
A : □□, □□, □□, □□□□□ □□. RKSfluid □□□□□□ □□ □□□ □□□□□. □□□ □□ □□□ □ □□□□.

Q : □□ □□□ □□□□□?
A : RKSfluid□□ □ □□ □□□□□ □□□ □□□ □□ □ □ □□□□.

Q : □□ □□ □□
A : □□ □□□ □□ □□□□ □□□ □□ 2 ~ 5 □□ □□□□□. □□□ □□□ □□ □□□

Q : MOQ
A : □□ □□□ 1pc□□□.

Q : □□ □□□ □□□□□?
□□ : □□ □□ 100 % □□ □□, 2 □ □□. □□□□ □□□□ □□□□□ □□□□□□.
□□□ TUV, API, WRAS, CE, ISO □□□ □□□□□□.
□ □□□ DIN, ASME, BS EN, JIS, API, AWWA□ □□□□□.

Q : □□□□ □□□ □□□□ □□□ □□□□□?
A : RKSfluid□ 20 □□ □□□ □□□□ □□□ 70 □ □□□ R & D □□□□□ □□ □□, □□ □□ □ □□ □□□ □□□□□.