



公司 : 上海 瑞科 流体 控制 有限公司
 产品 规格 : DN50-DN2400 (NPS1 1 / 4-NPS96)
 压力 : PN6 / PN10 / PN16 / PN25 (ANSI 150) / SABS 1123 1000/3 1600/3
 温度 : -29 °C ~ + 120 °C
 材质 : 阀体 : GGG40
 密封 : NR, NBR, EPDM, Viton, PTFE / PTFE
 球体 / 阀芯 : 316L 不锈钢, SS316, SS304, 钛合金, 铜合金, 铝
 阀座 : SS316, SS304, SS420, SS416, 2CR13, SS410
 口径 : 1/2", 3/4", 1", 1 1/2", 2", 3", 4", 6", 8", 10", 12", 15", 20", 24", 30", 36", 42", 48", 60", 72", 84", 96", 108", 120", 144", 168", 192", 216", 240"
 标准 : API, DIN, ASME, ISO, ANSI, GB / T, BS EN, AWWA
 认证 : CE, WRAS, API, ISO9001 : 2015, OHSAS18001 : 2007
 应用 : 石油, 化工, 冶金, 电力, 船舶, 暖通, 水利, 市政



Resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange



Resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: DI+ Nylon

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange



Resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange



Resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange



Double flange resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB, 5K/10K

Size:DN50-DN1000

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Flange



Short-neck butterfly valve for petroleum

ANSI 125LB/150LB

Top Flange Standard:ISO5211

Size:2"-12"

Body: DI CI

Disc :Stainless Steel

Seat : EPDM, NBR, Viton

Connection:Wafer, Lug



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: Ductile Iron+PTFE

Seat: PTFE

Connection: Wafer, Lug, Flange



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: Ductile Iron+PTFE

Seat: PTFE

Connection: Wafer, Lug, Flange



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB, CF8, CF8M

Disc: CF8+PTFE, CF8M+PTFE

Seat: PTFE

Connection: Wafer, Lug



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB, CF8, CF8M

Disc: CF8+PTFE, CF8M+PTFE

Seat: PTFE

Connection: Wafer, Lug



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: CF8, CF8M

Seat: PTFE

Connection: Wafer, Lug, Flange



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB

Disc: CF8 +PTFE, CF8 +PFA

Seat: PTFE

Connection: Wafer, Lug, Flange

APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



RKS Fluid 1997 年 成立。 公司 拥有 10 年 经验， 生产 各种 规格 阀门 产品。 公司 采用 CNC 加工 设备， 生产 精度高， 使用寿命长。 公司 拥有 完善 质量管理体系， 产品 符合 GB 标准。 公司 拥有 完善 售后服务 体系， 产品 销往 全球。 RKS 公司 生产 各种 规格 阀门 产品， 符合 CE、ADWO-2000、ISO9001、TS、API、TUV、GB、ISO 标准。 公司 拥有 完善 售后服务 体系， 产品 销往 全球。 "质量 第一， 客户 至上" 是 公司 宗旨。 公司 拥有 完善 售后服务 体系， 产品 销往 全球！

Our Factory



Exhibition Photos



Our Certificates

