

DN50-DN800, 2 2 .

- I- , , .
- II- .
- III- .
- IV- .
- V- .

-
- HVAC
-
-
-
-
-
-
-
-
-
-



DN	DN50 -DN800
PN	PN10 / PN16 / 150
Temp	-10 ° C ~+80 ° C
Material	GG25/GGG40/WCB/SS304/SS316/

□□	EPDM, NBR, □□
□□	□, □□, □□

COMPANY FACTORY



COMPANY INFORMATION



i 0000 00 : 00 00 00, 00 0 00 00 00.

CNC 00 00, 00 00 0, 0000 00 00, 00 00 00 0 00.

■ 00 00 00 000 000 0000000 000 00 00 00.

000 0000 000 0000 00 00 000 000000.

v 00 00 : GB, 00 00, 00 00, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRA, KTW, API 6D, API609.

VI 00 0000 : 00 00, 0 00, 000 00, 00 00, 000 00, 000 00, 00 / 00 / 00 00000, 00 00.

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06

COMPANY QUALIFICATION



COMPANY EXHIBITION



Partners



□□□□ □□:

Q : □□ □□ □□ □□ □□ □□□□?

A : □□ □□, □□, □□, □□, □□ □□□.

Q : □□□□□ □□ □ □ □□□□?

A : □□, □□, hydraulic, □□□□ □□.RKSfluid □□□□□ □□ □□ □□□□□.□□□ □□ □□ □□ □□ □ □□□□ □ □□□□.

Q : □□ □□ □□□□□?

A : RKSfluid□□ □□ □□ □□ □ □□ □ □□ □□ □□□□.

Q : □□ □□ □□

A : □□ □□ □□ 2 ~ 5 □□□□ □□ □□□□□.□□□ □□ □□ □□ □□.

Q : **MOQ**

A : □□ □□ □□ 1pc.

Q : □□ □□ □□□□□?

A : □□ □ 100% □□ □□□, 2 □ □□□□ □□□□ □□□□□□□□.

TUV, API, WRA, CE, ISO □□□ □□□□□□.

□□□ DIN, ASME, BS EN, JIS, API, AWWA□ □□□□□□.

Q : □□□□ □□ □□□□ □□ □□ □ □ □□□□?

A : RKSfluid □□□ 20 □ □□□ 70 □ □□□ R & D □□□□□ □□ □□, □□ □□ □ □□ □□□ □□□□□.