



DESIGN FEATURES

DURABLE

- No-pin connection, 1 pc blow-out proof stem
- DI/CI Nodularity over 95%

ANTI-CORROSION

- Material: Epoxy powder:  , Earth Best!
- Coating Thickness: 200-250µm
- Spraying temp: over 200°C. Doesn't fade, even wipe with diethyl ether

QUALITY STANDARD

- 100% quality test, follow DIN, ASTM, JIS, GB/T, ISO, BS EN, API
- ONLY ONE Manufacturer get CE certification up to DN1800
- 2 years warranty. 15000 times On-off test, 30000 times Destructive experiment





APPLICATION SCENARIO



Industrial water
application



Power plant



Sea water
desalination



Water treatment



Water supply
and drainage



HAVC



Food and drug



Water transport



Our Factory



I 工厂地址：中国山东省，青岛经济技术开发区。

II 工厂占地面积 100,000 平方米，建筑面积 50,000 平方米，拥有 100 多名员工。

III 工厂拥有先进的生产设备和技术，能够生产各种规格和材质的工业阀门。

IV 工厂通过了 ISO 9001 质量管理体系认证，确保产品质量。

Prodotto 符合 : GB, 符合, 符合, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609.

VI 符合 : 符合, 符合, 符合, 符合, 符合, 符合, 符合 / 符合 / 符合 符合, 符合.

Our Certificates



Exhibition Photos



[illegible]