

Features



Air Release valve

Size range:DN25-DN300

Pressure ratings:PN10 PN16

Body:Ductile Iron

Trim:SS304 SS316 etc

Connection:ARVS/KARS-BPT threaded, KARX-Flanged

Working temperature: -10°C~+80°C

□□:

1. □□ □□□□□ □□□ □□□□ □ □□ □ □□ □□ □□□□□ □□ □□□.
2. □□ □□□□ □□ □□□□ □ □□ □□ □□□ □□□ □□ □□□□ □□ □□□□.
3. □□ □□□□□ Bottom □□ □□□ □□□□ □□ □□□□ □□ □□□□ □□ □□□□□.
4. □□ □□ □□□ □□□□ □□ □□ □□□□ □□, □□, □□ □□□ □□□□□.
5. comply bs en 1074-4



DN25-DN50



DN50-DN300

Our Factory



RKSfluid 1997 年 成立。 拥有 Foundry 车间， 配备 各种 规格 的 铸 造 设备。 拥有 CNC 车 床， 钻 床， 铣 床 等 精 加 工 设备。 拥有 各种 规格 的 机 床。 拥有 各种 规格 的 机 床。 拥有 各种 规格 的 机 床。

Liaoning Province, GB

RK

GB, ISO, CE, ADWO-2000, TUV

ISO9001, TS, API

"

i

CNC

■

v GB, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRA, KTW, API 6D, API609.

VI

Our Certificates



Exhibition Photos

