

DESIGN FEATURES



● TECHNICAL REQUIREMENT

- 1.Design standard:BS 5163.
- 2.Face to face:BS 5163.
- 3.Flanges standard:BS EN1092-2:1997 PN16.
- 4.Test standard:BS EN12266-1 Rate B.

● FEATURES

- Double flange metal seated gate valve
- Size Range:DN50-DN2000
- Standard-ISO/BS/DIN/AWWA/API
- Tests Standard-BS EN 12266-1
- Body Ring-Bronze/SS420/SS304/SS316
- Body-Ductile Iron /Cast Iron/Stainless Steel /WCB
- Fusion bonded epoxy coating-min 300 microns



RELATED PRODUCTS



SMALL DIAMETER GATE VALVE
DN50-DN300,PN10/16/25



METAL SEATED GATE VALVE
DN350-DN600,PN10/16/25



LARGE DIAMETER METAL SEATED GATE VALVE
DN700-DN2000,PN10/16/25

APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



COMPANY INFORMATION



I 00 00: 00 000 00, 00 0 00 00 00.

II 00 CNC 00 00, 00 00 0, 000 00 00, 00 00 00 0 00.

III 00 00 00 000 00 00 00 00 000000.

VI 00 0000 0000 00000000 00000000.

V 00 00: GB, 00 00, 00 00, Tuv CE, ISO 9001, ADWO-200, TS, PED, WRC WRAS, KTW, API 6D, API609.

00 000: 000000 00, 0 00, 0000 00, 0000 00, 0000 00, 00 00, 00/00/00 000000, 00 00.



01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06

COMPANY QUALIFICATION



COMPANY EXHIBITION



Partners



□□□□ □□

Q: □□ □□ □□ □□ □□ □□□□?

□: □□ □□, □□, □□, □□, □□ □□□.

Q: □□□□□ □□ □ □□□? □□ □□ □□□□?

□□: □□□, □□□, □□□, □□□□□ □□. RKSfluid □□□□□□ □□ □□□ □□□□□□. □□□□□ □□□ □□□□.

Q: □□ □□ □□ □□□?

□: RKSfluid □□□ □□□ □□ □□□ □□□ □ □□ 4□□ □□□ □□□□□.

D: □□ □□ □□

□: □□ □□□ □□□ □□ 2~5□ □□□ □□□ □□□□□□. □□□ □□□ □□ □□□□□□□□□□.

□: **MOQ**

□: □□ □□□ □□ 1pc.

Q: □□ □□□ □□□ □□□?

A: □□ □ 100% □□ □□□, 2□ □□. □□ □□□□ □□ □□□□□□□□.

□□□ Tuv, Api, Wras, CE, ISO □□□ □□□□□□□□.

□□□ DIN, ASME, BS EN, JIS, API, Awwa□ □□□□□□.

Q: □□□□ □□□ □□□ □□□□ □□ □ □□□?

A: RKSfluid 27□□ □□□ □□□□ □□□□ 70□ □□□ R&D □□□□□ □□ □□, □□ □□ □ □□ □□□ □□□□□□.