

000_00 00 000 0000 000 000 000 0000 0000 0 00000.000 00 0 0 00 0000, 00, 00 0000 000000 00
00 0000 000 000000 000 0000000 0 000000.

000 00 : EN1092-2 / BS4504

00 00 : DIN F4 / DIN F5 / BS 5163

DESIGN FEATURES



Features



- Use AkzoNobel material.
- Super Anti-corrosion
- Epoxy powder coating 200-250um,
- Baking varnish over 200°C,

NO.		
1	Body	GGG50
2	Dise	GGG40+EPDM
3	Wedge nut	C48600
4	Stem	SS431
5	Bonnet	GT450-10
6	Gasket	EPDM
7	Y-ring	EPDM85-90
8	Fix ring	CuZn21Si3/C69300
9	Thrust bearing	C69300
10	Seal ring	EPDM70
11	O ring	NBR
12	Retainer ring	POM
13	Bushing ring	POM
14	Gland	SS431
15	Dustproof ring	EPDM85
16	Dise core	GGG40
17	Bolt	SS316





Free wedge nut, reduces the stem bending forces and at the same time enables it to be easily replaced.



The more compact new cap, reduces the water retention areas in order to reduce the risk of bacterial growth.



One piece stainless steel stem in for better resistance to axial load and to with stand higher operating torques.



Three locking tab for bayonet system prevents self-dismantling.



Dust guard integrating three O-ring shape, prohibiting the introduction of foreign bodies at the stem.



Male guiding system with composite sliding skate reduces the wear of the wedge against the body, allowing a smooth functionality and a longer life time of the valve.



Triple seal at the operating stem to ensure tightness with the test of time (2500 cycles).



New male composite sliding skate technology ensuring a low operating torque even under high differential pressure and preventing damage or corrosion generated by the friction.



APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



COMPANY FACTORY



COMPANY INFORMATION



i 0000 00 : 00 00 00, 00 0 00 00 00.

CNC 00 00, 00 00 0, 0000 00 00, 00 00 00 0 00.

0 00 00 00 000 000 0000000 0000 00 00 00.

000 0000 000 00000 00 00 000 0000000.

v 00 00 : GB, 00 00, 00 00, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609.

VI 00 0000 : 00 00, 0 00, 0000 00, 00 00, 0000 00, 0000 00, 00 / 00 / 00 000000, 00 00.

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06

COMPANY QUALIFICATION



COMPANY EXHIBITION



Partners



Delivery



Payment



FAQ

Q : What are your main products?

A : valves, pumps, actuators, etc.

Q : What are your main markets?

A : USA, Europe, hydraulic, etc. RKSfluid is a leading manufacturer of valves and pumps in the world.

Q : How long is your lead time?

A : RKSfluid can deliver valves and pumps in 4 weeks.

Q : How long is your warranty?

A : We provide 2 ~ 5 years warranty.

Q : MOQ

A : 1 pc.

Q : What are your certifications?

A : We have 100% ISO 9001, 2 ISO 14001. We are certified by TUV, API, WRA, CE, ISO 9001. We also have DIN, ASME, BS EN, JIS, API, AWWA.

Q : How long is your R & D period?

A : RKSfluid has 20 years R & D experience.