

DESIGN FEATURES



● TECHNICAL REQUIREMENT

- 1.Design standard:BS 5163.
- 2.Face to face:BS 5163.
- 3.Flanges standard:BS EN1092-2:1997 PN16.
- 4.Test standard:BS EN12266-1 Rate B.

● FEATURES

- Double flange metal seated gate valve
- Size Range:DN50-DN2000
- Standard-ISO/BS/DIN/AWWA/API
- Tests Standard-BS EN 12266-1
- Body Ring-Bronze/SS420/SS304/SS316
- Body-Ductile Iron /Cast Iron/Stainless Steel /WCB
- Fusion bonded epoxy coating-min 300 microns



RELATED PRODUCTS



SMALL DIAMETER GATE VALVE
DN50-DN300,PN10/16/25



METAL SEATED GATE VALVE
DN350-DN600,PN10/16/25



**LARGE DIAMETER
METAL SEATED GATE VALVE**
DN700-DN2000,PN10/16/25

APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



COMPANY INFORMATION



I 00 00: 00 000 00, 00 0 00 00 00.

II 00 CNC 00 00, 00 00 0, 000 00 00, 00 00 00 0 00.

III 00 00 00 000 00 00 00 00 000000.

VI 鋼 鋼鋼 鋼鋼 鋼鋼鋼鋼鋼 鋼鋼鋼鋼鋼.

V 鋼 鋼: GB, 鋼 鋼, 鋼 鋼, Tuv CE, ISO 9001, ADWO-200, TS, PED, WRC WRAS, KTW, API 6D, API609.

鋼 鋼: 鋼鋼鋼 鋼, 鋼 鋼, 鋼鋼 鋼, 鋼鋼 鋼, 鋼鋼 鋼, 鋼 鋼, 鋼/鋼/鋼 鋼鋼鋼, 鋼 鋼.



01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06

COMPANY QUALIFICATION



COMPANY EXHIBITION



Partners



Delivery



Payment



FAQ

Q: 如何付款？

答：电汇，支票，信用证，现金。

Q: 如何运输？

答：海运，空运，陆运，铁路。RKSfluid 可根据客户要求提供多种运输方案。

Q: 鋼 鋼管 鋼管 鋼管?

鋼: RKSfluid 鋼管 鋼管 鋼 鋼管 鋼管 鋼 鋼 4mm 鋼管 鋼管。

D: 鋼 鋼 鋼

鋼: 鋼 鋼管 鋼管 鋼 2~5mm 鋼管 鋼管 鋼管。 鋼管 鋼管 鋼 鋼管鋼管鋼管。

鋼: **MOQ**

鋼: 鋼 鋼管 鋼 1pc.

Q: 鋼 鋼管 鋼管 鋼管?

A: 鋼 鋼 100% 鋼 鋼管, 2mm 鋼。 鋼 鋼管 鋼 鋼管鋼管。

鋼管 Tuv, Api, Wras, CE, ISO 鋼管 鋼管鋼管。

鋼管 DIN, ASME, BS EN, JIS, API, Awwa 鋼 鋼管鋼管。

Q: 鋼管 鋼管 鋼管 鋼管 鋼 鋼管?

A: RKSfluid 27mm 鋼管 鋼管 鋼管 70mm 鋼管 R&D 鋼管鋼管 鋼 鋼, 鋼 鋼 鋼 鋼 鋼管 鋼管鋼管。