

RKSfluid®



规格	DN32 - DN2400(NPS1 1/4-NPS96)
压力等级	PN6 - PN10 - PN16(ANSI 150)
温度范围	-40°C-120°C
适用介质	清水、海水、蒸汽、酸、碱。
密封材料	NBR, EPDM, 氟橡胶, 石墨, 石棉
连接形式	法兰, 螺纹, U-夹, 焊接

APPLICATION SCENARIO

							
Industrial water application	Power plant	Sea water desalination	Water treatment	Water supply and drainage	HAVC	Food and drug	Water transport



COMPANY INFORMATION



I 廠址: 廣東省 肇慶市, 肇慶市 肇慶縣 肇慶鎮.

II 廠 CNC 機床 廠, 鑄造 廠, 鍛造 廠 廠, 機床 廠 廠 廠.

III 廠 廠 廠 廠, 廠 廠 廠 廠 廠 廠 廠.

VI 廠 廠 廠 廠 廠 廠 廠 廠.

V 廠 廠: GB, 廠 廠, 廠 廠, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609.

VI 廠 廠: [www.zjz.com](#), 廠 廠, 廠 廠, 廠 廠, 廠 廠, 廠 廠, 廠 廠/廠 廠/廠 廠 廠 廠, 廠 廠.



01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06

COMPANY QUALIFICATION



COMPANY EXHIBITION



Delivery



Payment



□□□□ □□:

Q: □□□ □□□ □□ □□ □□□□□?

□: □□" □□, □□, □□, □□, □□ □□□.

Q: □□ □□□□ □□ □□□□□□ □□ □ □□□□?

□: □□□, □□□, □□□, □□□□□ □□. RKSfluid □□□□□□ □□ □□□ □□□□□. □□□ □□ □□□□ □□□□□.

Q: □□□ □□ □□□ □□□□□?

□: RKSfluid □□□ □□□ □□ □□□ □□□ □ □□ 4□□ □□□ □□□□□.

Q: □□ □□□□

□: □□ □□□ □□□ □□ 2~5□ □□□ □□□ □□□□□. □□□ □□□ □□ □□□ □□□□□□.

□□: **MOQ**

A: □□ □□□ □□ 1pc.

Q: □□ □□□ □□□□□□?

A: □□ □ 100% □□ □□□, □□ 2□. □□□ □□ □□□ □□□□□□.

□□□ TUV, API, WRAS, CE, ISO □□□ □□□□□□.

□□□ DIN, ASME, BS EN, JIS, API, AWWA □ □□□□□.

Q: □□□□ □□□ □□□ □□□□ □□ □ □□□?

A: RKSfluid 20□□ □□□ □□□□ □□□ 70□ □□□ R&D □□□□□ □□ □□, □□ □□ □ □□ □□□ □□□□□.