

RKSfluid®

RKSfluid



WRAS



CE

RKSfluid®

RKSfluid



WRAS



CE

RKSfluid®



RKSfluid®



RKSfluid®



RKSfluid

RKSfluid®



WRAS  **CE**



Resilient seat butterfly valve



Resilient seat butterfly valve



Resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: DI+ Nylon

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange



Resilient seat butterfly valve



Double flange resilient seat butterfly valve



Short-neck butterfly valve for petroleum

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB, 5K/10K

Size:DN50-DN1000

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Flange

ANSI 125LB/150LB

Top Flange Standard:ISO5211

Size:2"-12"

Body: DI CI

Disc :Stainless Steel

Seat : EPDM, NBR, Viton

Connection:Wafer, Lug



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: Ductile Iron+PTFE

Seat: PTFE

Connection: Wafer, Lug, Flange



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: Ductile Iron+PTFE

Seat: PTFE

Connection: Wafer, Lug, Flange



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB, CF8, CF8M

Disc: CF8+PTFE, CF8M+PTFE

Seat: PTFE

Connection: Wafer, Lug



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB, CF8, CF8M

Disc: CF8+PTFE, CF8M+PTFE

Seat: PTFE

Connection: Wafer, Lug



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: CF8, CF8M

Seat: PTFE

Connection: Wafer, Lug, Flange



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB

Disc: CF8 +PTFE, CF8 +PFA

Seat: PTFE


Connection: Wafer, Lug, Flange

DESIGN FEATURES

DURABLE

- No-pin connection, 1 pc blow-out proof stem
- DI/CI Nodularity over 95%

ANTI-CORROSION

- Material: Epoxy powder:  , Earth Best!
- Coating Thickness: 200-250µm
- Spraying temp: over 200°C. Doesn't fade, even wipe with diethyl ether

QUALITY STANDARD

- 100% quality test, follow DIN, ASTM, JIS, GB/T, ISO, BS EN, API
- ONLY ONE Manufacturer get CE certification up to DN1800
- 2 years warranty. 15000 times On-off test, 30000 times Destructive experiment





APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport

Our Factory



Exhibition Photos



RKSfluid 1997 年 成立。 公司 专注于
 流体 机械, 泵 及 阀门 的 研发 与 生产。 公司
 CNC 加工 精度, 加工 速度 快, 交货 周期 短
 产品 质量, 性能 稳定 可靠。 公司 拥有 先进
 的 设备。 公司 产品 广泛应用于 石油 石化
 行业, 公司 产品 符合 GB 标准 及
 国际 标准 要求。 公司 产品
 符合 国际 标准 要求 及 RKS 标准 要求
 产品, 质量, 交货 周期 短 且 可靠。 公司 产品 符合
 标准 : GB, ISO, 符合 欧盟 标准, CE 及 ADWO-2000 及 TUV 认证 标准,
 ISO9001, TS, API。 公司 产品 : 泵, 阀门 及 各种 工业 机械,
 产品 质量 稳定 可靠 且 性能 优异。 公司 产品, 性能 稳定 可靠。 公司
 产品 : 泵 类, 阀门, 球阀, 蝶阀, 隔膜 泵, 离心 泵, 各种 工业 机械,
 产品 质量。 公司 产品 符合 国际 标准 要求 且
 "符合 国际 标准, 性能 稳定 可靠 且 交货 周期 短" 的 产品
 公司 产品。 公司 产品 符合 国际 标准 要求!
 I 公司 产品 : 泵 类 产品, 阀门 及 各种 工业 机械。

II 公司 CNC 加工 精度, 加工 速度 快, 交货 周期 短 且 可靠。

III 公司 产品 符合 国际 标准 要求 且 性能 稳定 可靠。

IV 公司 产品 符合 国际 标准 要求 且 性能 稳定 可靠。

V 认证 : GB, ISO 9001, TUV CE, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609.

VI 认证 : ISO 14001, ISO 45001, ISO 9001, ISO 9001, ISO 9001, ISO / IEC / ISO 9001, ISO 9001.

Our Certificates

