

RKSfluid®



WRAS



CE

RKSfluid®



WRAS



CE

RKSfluid®



RKSfluid®

RKSfluid



WRAS



CE

RKSfluid®



RKSfluid®




RKSfluid

DESIGN FEATURES

DURABLE

- **No-pin** connection, 1 pc **blow-out proof stem**
- DI/CI Nodularity over **95%**

ANTI-CORROSION

- Material: Epoxy powder:  , Earth Best!
- Coating Thickness: **200-250µm**
- Spraying temp: over **200°C**. Doesn't fade, even wipe with diethyl ether

QUALITY STANDARD

- **100% quality test**, follow DIN, ASTM, JIS, GB/T, ISO, BS EN, API
- **ONLY ONE** Manufacturer get **CE** certification up to **DN1800**
- **2 years** warranty. **15000** times On-off test, **30000** times Destructive experiment





Resilient seat butterfly valve



Resilient seat butterfly valve



Resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: DI+ Nylon

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange



Resilient seat butterfly valve



Double flange resilient seat butterfly valve



Short-neck butterfly valve for petroleum

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB, 5K/10K

Size:DN50-DN1000

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Flange

ANSI 125LB/150LB

Top Flange Standard:ISO5211

Size:2"-12"

Body: DI CI

Disc :Stainless Steel

Seat : EPDM, NBR, Viton

Connection:Wafer, Lug



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: Ductile Iron+PTFE

Seat: PTFE

Connection: Wafer, Lug, Flange



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: Ductile Iron+PTFE

Seat: PTFE

Connection: Wafer, Lug, Flange



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB, CF8, CF8M

Disc: CF8+PTFE, CF8M+PTFE

Seat: PTFE

Connection: Wafer, Lug



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB, CF8, CF8M

Disc: CF8+PTFE, CF8M+PTFE

Seat: PTFE

Connection: Wafer, Lug



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: CF8, CF8M

Seat: PTFE

Connection: Wafer, Lug, Flange



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB

Disc: CF8 +PTFE, CF8 +PFA

Seat: PTFE

Connection: Wafer, Lug, Flange



APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



Our Factory



RKSfluid 1997 年 成立。 公司 生产
 各种 阀门, 球阀 等 工业 产品。 我们
 CNC 加工 各种 零件, 具有 丰富 经验
 和 技术, 能够 生产 各种 规格 产品。
 我们 拥有 先进 设备 和 技术 人员, 能够
 生产 各种 规格 产品。 GB 标准 产品
 我们 生产 各种 规格 产品。 我们 拥有
 丰富 经验 和 技术 人员, 能够 生产
 各种 规格 产品。 RKS 公司 生产
 各种 规格 产品。 我们 拥有 丰富 经验
 和 技术 人员, 能够 生产 各种 规格
 产品 : GB, ISO, 各种 规格 产品, CE 认证 ADWO-2000 认证 TUV 认证 产品,
 ISO9001, TS, API。 我们 拥有 : 各种 规格 产品, 各种 规格 产品, 各种
 规格 产品 等 各种 规格 产品。 我们 拥有 丰富 经验 和 技术 人员, 能够
 生产 各种 规格 产品 : 各种 规格 产品, 各种 规格 产品, 各种 规格 产品,
 各种 规格 产品。 我们 拥有 丰富 经验 和 技术 人员, 能够 生产 各种
 "各种 规格 产品, 各种 规格 产品" 等 各种 规格
 产品 等 产品。 我们 拥有 丰富 经验 和 技术 人员!
 I 我们 拥有 : 各种 规格 产品, 各种 规格 产品 等。

II 我们 CNC 加工 各种 零件, 具有 丰富 经验 和 技术 人员。

III 我们 拥有 各种 规格 产品 等 各种 规格 产品 等 各种 规格 产品。

IV 我们 拥有 各种 规格 产品 等 各种 规格 产品。

V 我们 拥有 : GB, 各种 规格 产品, 各种 规格 产品, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS,

KTW, API 6D, API609.

VI 00 000 : 00 000 00, 0 00, 000 00, 00 00, 000 00, 000 00, 00 / 00 / 00 00000, 00 00.

Our Certificates

