





RKSfluid®


A key Valve in Flow Control




Butterfly Valve



Ball Valve




Gate Valve



Globe Valve



Check Valve



Pipe Fittings

DESIGN FEATURES

RANGE

- For DI, AC, PVC and Fibre cement pipes
- Dimension from **32-315mm**



Ductile iron



Fibre
Cement



Poly Vinyl
Chloride

LOW COST

- Structure compact and **convenient operation**

RELIABLE

- **EPDM gasket** to EN681-1
- **Anti-corrosive** coating
- Bichromated bolts on series 790

MATERIAL

- S700 & S750: Grey Cast Iron **EN-GJL-250** Quality
- S790: ductile iron **EN-GJS-400-15** Quality

APPLICATION SCENARIO



Industrial water
application



Hydroelectric
generation



Sewagetreatment



Water treatment



Water supply
and drainage



Water transport



Pipe network
in house



Irrigation



Our Factory



Company Advantages

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06



I 100% high level ex-factory inspection.

II CNC processing, precision, accuracy, high quality.

III 100% high level ex-factory inspection.

IV 2 years quality assurance, repair and replacement.

V Certifications: GB, ISO 9001, TUV CE, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609.

