



- **Suitable** for viscous liquid, V-shaped gap, flow stability, not easy to block
- **High-strength** structure, mesh screen without deformation, high safety factor, flexible increase in the number of units
- The outer surface of the filter element is smooth and easy to clean. Automated operation, backwashing consumes less liquid
- Tolerate high-intensity positive and negative pressure
- Precision filtration, accuracy range **25-500** μm
- 304, 316L material, corrosion resistant

Our Factory



Company Advantages

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06



1. 鋼 鋼 鋼 鋼, 鋼 鋼 鋼 鋼, 鋼 鋼 鋼 鋼, 鋼 鋼 鋼 鋼 鋼 鋼, PP 鋼 鋼, 鋼 鋼, 鋼 鋼 鋼 鋼, 鋼 鋼, 鋼 鋼 鋼 鋼, 鋼 鋼 鋼 鋼, 鋼 鋼.
2. 鋼 鋼 鋼 鋼 鋼 鋼 鋼 鋼 鋼 鋼 鋼 鋼 10 鋼 鋼.
3. API, AWWA, ASME, BS EN, DIN, JIS 鋼 鋼, TUV, CE, ISO9001, TS, OHSAS, WRAS 鋼 鋼 鋼 鋼 鋼 鋼.
4. 鋼 鋼 鋼 鋼 鋼 鋼 R & D 鋼 鋼 鋼 鋼 鋼 - 鋼 鋼 鋼 鋼 鋼 鋼 鋼 鋼 鋼 鋼 鋼 鋼

Exhibition Photos



Our Certificates





RKSfluid®

Tel: 024 2318 0188-899

Email/Skype: ivory@rksfluid.com

Mobile/WhatsApp/Wechat: +86 15140071761

Add: Pump & Valve Industrial Park, No. 5 Panwu Road,
Liaozhong Dist. Shenyang, Liaoning P.R. China

□□□□ □□

Q1 : □□□ □□□ □□ □ □□□□?

A1 : □□□ □□, □□, □□□ □□□□□.

Q2 : □□ □□□ □□□□□?

A2 : □□□ □□ 5-10 □, □□ □□□ 15-90 □ □□□ □□.

Q3 : □□ □□□ □□□□□?

A3 : T / T 30 % □□, □□□□ □□ □□□ □□ □ □□ □□. □□ □□ □□□.

Q4 : □□□ MOQ□ □□□□□? □□ □□□ □ □ □□□□?

A4 : □□□ 1pc □□□ □□□ □ □□□□, □□□ □□□ □□□□ □□ □□□□□. □□□ □□ □□□□□□□.

Q5 : □□ □□□ □□□□□? □□ □□ □□ □□□ □□□□□?

A5 : □, 100 % □□□. □□□ □□□□ □□ □□□ □□□□□□.

Q6 : □□ □ □□□ □□ □□ □□□ □□□ □□ □ □ □□□□?

A6 : □□, □□□ □□ □□□ □□□□□□. □□□ □□□□□□ □□□□□ □□□□ □□□ □□ □□ □□□ □□□□□.

Q7 : □□□ □□□ □ □□□ □□□ □□□□□?

A7 : □□ □□□ 1 □□□□□. □□□ □□ □ □□□ □□, □□ □□□□□ □□□□□.