



## DESIGN FEATURES

### DURABLE

- No-pin connection, 1 pc blow-out proof stem
- DI/CI Nodularity over 95%

### ANTI-CORROSION

- Material: Epoxy powder:  , Earth Best!
- Coating Thickness: 200-250µm
- Spraying temp: over 200°C. Doesn't fade, even wipe with diethyl ether

### QUALITY STANDARD

- 100% quality test, follow DIN, ASTM, JIS, GB/T, ISO, BS EN, API
- ONLY ONE Manufacturer get CE certification up to DN1800
- 2 years warranty. 15000 times On-off test, 30000 times Destructive experiment







## APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport





# Our Factory



## Company Advantages

01

21 years of professional experience

03

Independent research and development team  
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06





□ □ □ □ : □ □ □ □ □ □, □ □ □ □ □ □ □ □.

□ □ □ CNC □ □ □ □ □ □, □ □ □ □ □ □, □ □ □ □ □ □ □ □ □ □ □ □.

□ □.

☒ □ □ □ □ □ □ □ □ □ □ (Houston) □ □ □ □ □ □ □ □ □ □ □ □.

◆ □ □ □ □ : GB, □ □ □ □, □ □ □ □, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609.

VI □ □ □ □ : □ □ □ □ □ □, □ □ □ □, □ □ □ □ □ □, □ □ □ □, □ □ □ □ □ □, □ □ □ □ □ □, □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □.

## Exhibition Photos



# Our Certificates



□□□□ □□

Q : □□□□ □□□□ □□ □□□ □□□□□?

A : □□□ □□, □□, □□, □□, □□ □□□.

Q : □□□□□□ □□ □ □ □□□□?

A : □□□, □□, □□, □□□□□ □□. RKSfluid □□□□□□ □□ □□□ □□□□□□. □□□ □□□□□□, □□ □□□□□□□.

Q : □□□ □□ □□□ □□□□□?

A : RKSfluid□□ □□□ □□□ □□ □ □□□ 4 □□ □□□ □□□□□.

Q : □□ □□ □□

A : □□□□ □□□ 2 ~ 5 □ (2 ~ 5 □)□ □□□□□. □□□□ □□□ □□ □□□ □□ □ □□.

Q : MOQ.

A : □□ □□□ □□ 1pc.

Q : □□ □□□ □□□□□?

A : □□ □□ 100 % □□ □□□, 2 □ □□. □□□□ □□□□□ □□□□□.

□□□ TUV, API, WRAS, CE, ISO □□□□ □□□□□□.

□□, DIN, ASME, BS EN, JIS, API, AWWA.

Q : □□□□ □□□ □□□□ □□ □ □ □□□□?

A : RKSfluid 20 70 R & D ,