RKSfluid®
A key Valve in Flow Control
Butterfly Valve
Ball Valve
Gate Valve
Globe Valve
Check Valve
Pipe Fittings

DESIGN FEATURES

VERSATILE & RANGE

- Up to 27mm of tolerance, DN40 ~ DN300 stock reduction
- Allows angular deflection of +/-5°
- Covering most common pipe materials

DI — Ductile Iron
CI — Cast Iron
PVC — Poly Vinyl Chloride
STL — Steel
GRP — Glass fibre reinforced plastic
AC — Fibre Cement

USER FRIENDLY

- Economical and applicable
- Easy Operation

OPTIMAL SEALING

- Unique gasket with circumferential ribs sealing on corroded, scored or pitted pipes

DURABLE

- Anti-corrotion
- Thickness: Epoxy powder coating of 200-250μm
- Temperature : Spraying temperature over 200 ℃. Doesn't fade, even wipe with diethyl ether

MATERIAL

- Epoxy powder: AkzoNobel, Earth Best!
- Nuts: DACROMET® or GEOMET®, Earth Best!
- Cast iron: EN-GJS-500-7, nodularity over 95%!

APPLICATION SCENARIO

Industrial water application | Hydroelectric generation | Sewagetreatment | Water treatment | Water supply and drainage | Water transport | Pipe network in house | Irrigation

Our Factory

I □□ □□ : □□ □□ □□, □□ □ □□ □□ □□.

II □□ CNC □□□ □□, □□ □□ □, □□ □□, □□ □□ □□ □ □□.

III □□□ □□ □□ □□, □□ □□ □□ □□ □□□ □□□□□.

IV □□ □□□ □ □□□□ □□ □□ □□□ □□□□□□.

V □□ □□ : GB, □□ □□, □□ □□, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609.

VI □□ □□ : □□ □□□ □□, □ □□, □□□ □□, □□ □□, □□□ □□, □□□ □□, □□ / □□ / □□ □□□□□, □□ □□.

□□□□ □□

Q : □□□ □□□ □□ □□ □□□ □□□□□?
A : □□□ □□, □□, □□, □□, □□ □□□.

Q : □□□□□ □□□□□□ □□ □ □ □□□□?
A : □□, □□, Hrdraulic, □□□□□ □□. RKSfluid □□□□□□ □□ □□□ □□□□□. □□□ □□ □□□□□.

Q : □□ □□□ □□□□□?
A : RKSfluid□□ □□□ □□□ □□ □ □□□ 4 □□ □□□ □□□□.

Q : □□ □□ □□

A : □□□□ □□□□ 2 ~ 5 □□ □ □□ □□□ □□□□. □□□ □□□ □□ □□□ □□.

Q : MOQ
A : □□ □□□□□ 1pc.

Q : □□ □□□ □□□□□?
A : □□□ □□ 100 % □□ □□□, □□ 2 □. □□□ □□ □□□ □□□□□□.
□□□ TUV, API, WRAS, CE, ISO □□□ □□□□□.
□□□ DIN, ASME, BS EN, JIS, API, AWWA□ □□□□□.

Q : □□□□ □□□ □□□□ □□□ □□ □ □ □□□□?
A : RKSfluid□ 20 □□ □□□ □□□□ □□□ 70 □ □□□ R & D □□□□□ □□ □□, □□ □□ □ □□ □□□ □□□□□.