

DESIGN FEATURES

DURABLE




- No-pin connection, 1 pc blow-out proof stem
- DI/CI Nodularity over 95%

ANTI-CORROSION

- Material: Epoxy powder:  , Earth Best!
- Coating Thickness: 200-250µm
- Spraying temp: over 200°C. Doesn't fade, even wipe with diethyl ether


QUALITY STANDARD

- 100% quality test, follow DIN, ASTM, JIS, GB/T, ISO, BS EN, API
- ONLY ONE Manufacturer get CE certification up to DN1800
- 2 years warranty. 15000 times On-off test, 30000 times Destructive experiment



□□	DN32 - DN2400(NPS1 1/4-NPS96)
□□ □□	PN6 - PN10 - PN16(□□□ 150)
□□ □□	-40°C-120°C

□□	□□□□ □□ □, □□□□□□ □.
□□ □□	NBR, EPDM, □□□□□, □□□□, □□□□
□□	□□□□, □□, U-□□, □□ □□□□



NPS14-NPS40 Wafer/Lug with alignment holes													
Size	L	H1	H2	h	A	ΦB	C	ΦG	a	b	ΦD	n-Φd	IS05211
NPS14	3.07	10.63	11.81	1.42	1.06	Φ13.31	12.95	-	-	-	Φ4.92	4-Φ0.55	F12
NPS16	4.02	11.81	13.58	1.69	1.26	Φ15.35	14.80	-	-	-	Φ5.50	4-Φ0.71	F14
NPS18	4.49	12.99	14.76	1.93	4.42	Φ17.20	16.61	-	-	-	Φ5.50	4-Φ0.71	F14
NPS20	5.00	15.16	16.73	2.56	-	Φ19.09	18.43	Φ2.36	0.71	2.52	Φ6.50	4-Φ0.87	F16
NPS24	6.06	17.24	19.49	2.76	-	Φ23.03	22.24	Φ2.36	0.71	2.52	Φ6.50	4-Φ0.87	F16
NPS28	6.50	20.39	22.44	3.15	-	Φ26.77	25.98	Φ2.76	0.79	2.93	Φ10.00	8-Φ0.71	F25
NPS30	6.50	21.46	24.02	3.15	-	Φ28.74	27.95	Φ2.76	0.79	2.93	Φ10.00	8-Φ0.71	F25
NPS32	7.48	22.32	25.20	3.15	-	Φ30.43	29.49	Φ2.76	0.79	2.93	Φ10.00	8-Φ0.71	F25
NPS36	7.99	25.59	27.56	3.94	-	Φ34.49	33.54	Φ3.15	0.87	3.35	Φ10.00	8-Φ0.71	F25
NPS40	8.50	28.15	29.53	3.94	-	Φ38.43	37.48	Φ3.15	0.87	3.35	Φ11.73	8-Φ0.87	F30

APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



COMPANY INFORMATION



I 廠址: 廣東省 肇慶市, 肇慶市 肇慶市 肇慶市.

II 廠 CNC 廠房 廠房, 廠房 廠房 廠房, 廠房 廠房 廠房.

III 廠房 廠房 廠房, 廠房 廠房 廠房 廠房.

VI 廠 廠房 廠房 廠房 廠房 廠房.

V 廠 廠: GB, 廠 廠, 廠 廠, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609.

VI 廠 廠: 廠 廠, 廠 廠, 廠房 廠房, 廠房 廠房, 廠房 廠房, 廠房 廠房, 廠房/廠房/廠房 廠房, 廠房.



01

21 years of professional
experience

03

Independent research and
development team
28 top senior professional
researchers

05

100% high level ex-factory
inspection

07

2 years quality assurance,
repair and replacement

4 factories

02

2 professional testing
centers

04

High quality imported
materials

06

COMPANY QUALIFICATION



COMPANY EXHIBITION



Partners



Delivery



Payment



FAQ:

Q: 如何付款?
A: 电汇, 支票, 信用卡, 支付宝, 微信支付.

Q: 如何运输?
A: 海运, 空运, 陆运, 铁路. RKSfluid 提供多种运输方式. 客户可根据需求选择.

Q: 如何包装?
A: RKSfluid 提供多种包装方式, 可根据客户需求定制.

Q: 鋼 鋼管

鋼: 鋼 鋼管 鋼管 鋼 2~5 鋼管 鋼管 鋼管. 鋼管 鋼管 鋼 鋼管 鋼.

鋼: **MOQ**

A: 鋼 鋼管 鋼 1pc.

Q: 鋼 鋼管 鋼管?

A: 鋼 鋼 100% 鋼 鋼管, 鋼 2. 鋼管 鋼 鋼管 鋼管.

鋼管 TUV, API, WRAS, CE, ISO 鋼管 鋼管.

鋼管 DIN, ASME, BS EN, JIS, API, AWWA 鋼管.

Q: 鋼管 鋼管 鋼管 鋼管 鋼 鋼管?

A: RKSfluid 20 鋼管 鋼管 鋼管 70 鋼管 R&D 鋼管 鋼管 鋼, 鋼 鋼 鋼 鋼管 鋼管.