

RKSfluid®



RKSfluid®



RKSfluid®



RKSfluid®




DESIGN FEATURES

DURABLE

- No-pin connection, 1 pc blow-out proof stem
- DI/CI Nodularity over 95%

ANTI-CORROSION

- Material: Epoxy powder:  , Earth Best!
- Coating Thickness: 200-250µm
- Spraying temp: over 200°C. Doesn't fade, even wipe with diethyl ether

QUALITY STANDARD

- 100% quality test, follow DIN, ASTM, JIS, GB/T, ISO, BS EN, API
- ONLY ONE Manufacturer get CE certification up to DN1800
- 2 years warranty. 15000 times On-off test, 30000 times Destructive experiment





APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



RKSfluid 1997 年 創 始 於 德 國。 專 業 研 究 和 開 發
 各 種 工 業 用 水 閥 門 及 配 件。 採 用
 CNC 精 確 加 工， 確 保 質 量 和 精 度。

00 00, 00 00 0 00 00. 000 000 00 0000000.
00 00. 00 000 000 000 000000 000 000 00
000 0, 00 00 00 000 00 GB000 00
00 00 00 00 00. 0000 00
00 0000 0 00 00 00 0 RKS 00 00
00, 00, 00000 000 0 00. 00 000 00000. 000 00 00 00
00 : GB, ISO, 00 0 00 00, CE 0 ADWO-2000 00 TUV 00
ISO9001, TS, API. 000 00 : 00, 00 0 00 00 0 00,
00 000 00 0 000 00. 00 00, 00 00 00. 00 0
00 : 00 00, 00, 000, 00, 00 00, 00 00 0, 000 000,
00 00. 0000 00 000 000 00 0000 000 000000.
"00 0 00, 000 00 0 0000 00"0 000000
00 00 00. 00 000 000 00 000000!
I 00 00 : 00 00 00, 00 0 00 00 00.

II 00 CNC 000 00, 00 00 0, 00 00, 00 00 00 0 00.

III 00 00 00 000 000 0000 00 000 00 00 00.

IV 00 000 0000 00 00 000 00000.

V 00 00 : GB, 00 00, 00 00, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609.

VI 00 000 : 00 000 00, 0 00, 000 00, 00 00, 000 00, 000 00, 00 / 00 / 00 00000, 00 00.

Company Advantages



Our Certificates



Our Factory

