



Name	Material
Body	GGG50
Disc	GGG40+EPDM
Wedge nut	C48600
Stem	SS431
Bonnet	GT450-10
Gasket	EPDM
Y-ring	EPDM85-90
Fix ring	CuZn21Si3/C69300
Thrust bearing	C69300
Seal ring	EPDM70
O ring	NBR
Retainer ring	POM
Bushing ring	POM
Gland	SS431
Dustproof ring	EPDM85
Disc core	GGG40
Bolt	SS316

Product Description



Super Anti-corrosion
Epoxy powder coating **200-250µm**,
baking varnish over **200°C**,
use  material.



Free wedge nut, **reduces the stem bending forces** and at the same time enables it to be easily replaced.



The more compact new cap, reduces the water retention areas in order to **reduce the risk of bacterial growth**.



One piece stainless steel stem in for **better resistance to axial load and to with stand higher operating torques**.



Three locking tab for bayonet system prevents self-dismantling.



Dust guard integrating three O-ring shape, **prohibiting the introduction of foreign bodies** at the stem.



Male guiding system with composite sliding skate reduces the wear of the wedge against the body, allowing a smooth functionality and a longer life time of the valve.



Triple seal at the operating stem to ensure tightness with the test of time (2500 cycles).



New male composite sliding skate technology ensuring a low operating torque even under high differential pressure and preventing damage or corrosion generated by the friction.

Design standard

Design standard	BS EN 1171 ANSI
Flange	GB/T 17241.6-2008、 DIN 2633-1975、 BS EN1902-2
Face to face	GB/T 12221-2005、 ISO 5752-1988、 BS EN558-1(F4、 F5)
Test standard	EN12266

Specification

Size	DN50-900
Pressure	PN10 PN16 class150
Medium	Water
Temperature	0°C~90°C

PRODUCT DISPLAY



SHIPPING PACKAGING



COMPANY INFORMATION



1 00 00 : 00 00 00, 00 0 00 00 00.

00, 00 000 00, 00 000 00 00, 00 00 00 0 00 00 || 00 CNC.

III 閘門 閘門 閘門 閘門, 閘門 閘門 閘門 閘門 閘門 閘門。

IV 閘門 閘門, 閘門, 閘門 閘門 閘門 閘門 閘門。

V 閘門 閘門 : GB, 閘門 閘門, 閘門 閘門, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609.

VI 閘門 閘門 : 閘門 閘門 閘門, 閘門 閘門, 閘門 閘門, 閘門 閘門, 閘門 閘門, 閘門 閘門 閘門 / 閘門 / 閘門 閘門 閘門, 閘門 閘門。



EXHIBITION



COMPANY INFORMATION



□□□□ □□

Q : □□ □□□□□□ □□, □□ □□ □□ □□□□?

A : □□ '□□, □□, □□, □□, Application □□□.

Q : □□□ □□□□□ □□ □ □□□□, □□□ □□□?

A : □□, □□, Hrdraulic, □□□□□ □□. RKSfluid □□□□□□ □□ □□□ □□□□. □□□ □□□□□ □□ □□□□□□□.

Q : □□□ □□ □□□ □□□□□?

A : RKSfluid□ □□□ □□□□□ □□□ □□ □ □□□ □ □□ □□□□□□□.

Q : □□ □□ □□

A : □□ □□□ 2 ~ 5 □□ □□□ □□□. □□□ □□□ □□□ □□.

Q : MOQ

A : □□ □□□ 1 □.

Q : 100% 100% 100%?

A : 100% 100% 100%, 2 100%. 100% 100% 100%.

100% TUV, API, WRAS, CE, ISO 100% 100%.

100% DIN, ASME, BS EN, JIS, API, AWWA 100%.

Q : 100% 100% 100% 100% 100% 100%?

A : RKSfluid 100% 20 100% 70 100% R & D 100% 100%, 100% 100% 100% 100%.