




RKSfluid®

A key Valve in Flow Control



Butterfly Valve



Ball Valve




Gate Valve



Globe Valve



Check Valve



Pipe Fittings

Product Description



Super Anti-corrosion
Epoxy powder coating **200-250µm**,
baking varnish over **200°C**,
use  material.



Free wedge nut, **reduces the stem bending forces** and at the same time enables it to be easily replaced.



The more compact new cap, reduces the water retention areas in order to **reduce the risk of bacterial growth**.



One piece stainless steel stem in for **better resistance to axial load and to with stand higher operating torques**.



Three locking tab for bayonet system prevents self-dismantling.



Dust guard integrating three O-ring shape, **prohibiting the introduction of foreign bodies** at the stem.



Male guiding system with composite sliding skate reduces the wear of the wedge against the body, allowing a smooth functionality and a longer life time of the valve.



Triple seal at the operating stem to ensure tightness with the test of time (2500 cycles).



New male composite sliding skate technology ensuring a low operating torque even under high differential pressure and preventing damage or corrosion generated by the friction.

□□ □□: **TLG** □□ □□ □□ □□□□ □□ □□

DESIGN FEATURES

TECHNICAL REQUIREMENT :

- 1.Design standard: BS 5163.
- 2.Face to face: BS 5163.
- 3.Flanges standard: BS EN1092-2: 1997 PN16.
- 4.Test standard: BS EN12266-1 Rate B.

FEATURES :

- ◆ Double flange metal seated gate valve
- ◆ Size Range: DN50-DN2000
- ◆ Standard -ISO / BS /DIN / AWWA /API
- ◆ Tests Standard-BS EN 12266-1
- ◆ Body Ring-Bronze /SS420 /SS304 /SS316
- ◆ Disc Ring-Bronze /SS420 /SS304 /SS316
- ◆ Stem-Stainless Steel SS420 /SS431 /SS316
- ◆ Body-Ductile Iron / Cast Iron/Stainless Steel /WCB
- ◆ Disc-Ductile Iron /Cast Iron/Stainless Steel /WCB
- ◆ Fusion bonded epoxy coating-min 300 microns



RKS SMALL DIAMETER GATE VALVE
DN50 - DN300, PN10 / 16 /25

RKS METAL SEATED GATE VALVE
DN350 - DN600, PN10 / 16 /25

RKS LARGE DIAMETER METAL SEATED GATE VALVE
DN700 - DN2000, PN10 / 16 /25

APPLICATION SCENARIO





I 鋼 鋼 : 鋼 鋼 鋼, 鋼 鋼 鋼 鋼.

II 鋼 CNC 鋼 鋼, 鋼 鋼 鋼, 鋼 鋼 鋼 鋼, 鋼 鋼 鋼 鋼.

III 鋼 鋼 鋼 鋼 鋼 鋼 鋼 鋼 鋼 鋼 鋼.

IV 鋼 鋼 鋼 鋼 鋼 鋼 鋼 鋼.

V 鋼 鋼 : GB, 鋼 鋼, 鋼 鋼, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609.

VI 鋼 鋼 : 鋼 鋼 鋼, 鋼 鋼, 鋼 鋼 鋼, 鋼 鋼, 鋼 鋼 鋼, 鋼 鋼 鋼, 鋼 / 鋼 / 鋼 鋼 鋼 鋼, 鋼 鋼.

Four factories



Why choose us



Our Factory



Exhibition Photos



Our Certificates



□□□□ □□

Q : □□□ □□□ □□ □□ □□□□□□?

A : □□ □□, □□, □□, □□, □□ □□□.

Q : □□□□□□ □□ □ □ □□□□?

A : 鋼管, 鋁管, 銅管, 不銹鋼管 等. RKSfluid 鋼管鋼管 鋼管 鋼管 鋼管. 鋼管 鋼管, 鋼管 鋼管.

Q : 鋼管 鋼管 鋼管?

A : RKSfluid 鋼管 鋼管 鋼管 鋼管 鋼管 4 鋼管 鋼管 鋼管.

Q : 鋼管 鋼管 鋼管

: 鋼管 鋼管 鋼管 2 ~ 5 鋼管. 鋼管 鋼管 鋼管 鋼管.

Q : MOQ

: 1 鋼管 鋼管 鋼管.

Q : 鋼管 鋼管 鋼管?

: 100 % 鋼管 鋼管 鋼管 鋼管 2 鋼管. 鋼管 鋼管 鋼管 鋼管.

鋼管 TUV, API, WRAS, CE, ISO 鋼管 鋼管.

鋼管 DIN, ASME, BS EN, JIS, API, AWWA 鋼管.

Q : 鋼管 鋼管 鋼管 鋼管 鋼管 鋼管?

A : RKSfluid 鋼管 20 鋼管 鋼管 鋼管 鋼管 70 鋼管 R & D 鋼管 鋼管 鋼管, 鋼管 鋼管 鋼管 鋼管 鋼管.