

DESIGN FEATURES



DURABLE :

- 1 piece non-welded PFA molded DSS Disc stem
- Precision casting WCB/CF8M Bodies

TRIPLE SEAL:

- Triple Seal:Spring loaded Mechanical seal,Radial Lip Seal,FPM
- China ONLY ONE Manufacturer 400Mpa Iso-static pressing PTFE seat,consistent density

ANTI-CORROSION:

- Material: Epoxy powder
- Coating Thickness:200-250 μ m
- Spraying temp: over 200 $^{\circ}$ C. Doesn't fade, even wipe with diethyl ether

QUALITY STANDARD

- 100% quality test, follow DIN, ASTM, JIS, GB/T, ISO, BS EN, API
- ONLY ONE Manufacturer get CE certification up to DN1800
- 2 years warranty.15000 times On off test,30000 times Destructive experiment



Wafer

Lug

IMPERIAL DIMENSIONS:Inches

| Size | L | H1 | H2 | h | A | B | C | D | d | ISO5211 |
|----------|------|------|-------|------|------|-------|-------|------|------|---------|
| NPS2 | 1.69 | 2.20 | 5.31 | 0.47 | 0.43 | 2.01 | 1.08 | 1.97 | 0.28 | F05 |
| NPS2 1/2 | 1.81 | 3.35 | 5.91 | 0.47 | 0.43 | 2.72 | 1.99 | 1.97 | 0.28 | F05 |
| NPS3 | 1.81 | 3.74 | 6.30 | 0.63 | 0.55 | 3.27 | 2.70 | 2.76 | 0.35 | F07 |
| NPS4 | 2.05 | 4.13 | 7.09 | 0.63 | 0.55 | 4.06 | 3.50 | 2.76 | 0.35 | F07 |
| NPS5 | 2.20 | 4.92 | 7.68 | 0.63 | 0.55 | 5.00 | 4.49 | 2.76 | 0.35 | F07 |
| NPS6 | 2.20 | 5.71 | 10.04 | 0.63 | 0.55 | 5.98 | 5.57 | 2.76 | 0.35 | F07 |
| NPS8 | 2.36 | 6.69 | 9.45 | 0.83 | 0.75 | 7.99 | 7.64 | 4.02 | 0.47 | F10 |
| NPS10 | 2.68 | 8.07 | 11.81 | 0.94 | 0.87 | 10.00 | 9.65 | 4.92 | 0.51 | F12 |
| NPS12 | 3.07 | 9.84 | 12.20 | 1.14 | 1.06 | 12.01 | 11.61 | 4.92 | 0.51 | F12 |

APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport





COMPANY INFORMATION



i 0000 00 : 00 00 00, 00 0 00 00 00.

CNC 00 00, 00 00 0, 0000 00 00, 00 00 00 0 00.

■ 00 00 00 000 000 000000 000 00 00 00.

000 0000 000 0000 00 00 000 000000.

v 00 00 : GB, 00 00, 00 00, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRA, KTW, API 6D, API609.

VI 00 0000 : 00 00, 0 00, 000 00, 00 00, 000 00, 000 00, 00 / 00 / 00 00000, 00 00.

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06

COMPANY QUALIFICATION



COMPANY EXHIBITION



Partners



□□□□ □□

Q : □□□ □□□ □□ □□ □□□□□□?

A : □□□ □□, □□, □□, □□, □□ □□□.

Q : □□□□□□ □□ □ □ □□□□?

A : □□, □□, hrdraulic, □□□□□ □□.RKSfluid □□□□□□ □□ □□□ □□□□□□.□□□ □□□ □□ □□ □□□□ □ □□□□.

Q : □□ □□□ □□□□□?

A : RKSfluid□□ □□□ □□□ □□ □ □□□ 4 □□ □□□ □□□□.

Q : □□ □□ □□

A : □□ □□□ 2 ~ 5 □□□□ □□□ □□□□.□□□ □□□ □□ □□□ □□.

Q : MOQ

A : □□ □□□ □□ 1pc.

Q : □□ □□□ □□□□□?

A : □□ □ 100% □□ □□□, 2 □ □□.□□□□ □□□□ □□□□□□.

TUV, API, WRA, CE, ISO □□□ □□□□□.

□□□ DIN, ASME, BS EN, JIS, API, AWWA□ □□□□□.

Q : □□□□ □□□ □□□□ □□□ □□ □ □ □□□□?

A : RKSfluid □□□ 20 □ □□□ 70 □ □□□ R & D □□□□□ □□ □□, □□ □□ □ □□ □□□ □□□□□.