



DESIGN FEATURES

VERSATILE & RANGE

- Up to 28mm of tolerance, **DN40 ~ DN450** stock reduction
- Allows angular deflection of **+/-3°** per gasket
- Covering most common pipe materials



OPTIMAL SEALING

- **Unique gasket** with circumferential ribs sealing on corroded, scored or pitted pipes

DURABLE

- **ANTI-CORROSION**
- Thickness: **Epoxy powder coating of 200-250µm**
- Temperature : **Spraying temperature over 200°C**
Doesn't fade, even wipe with **diethyl ether**

MATERIAL

- Epoxy powder: **AkzoNobel**, Earth Best!
- Nuts: **DACROMET®** or **GEOMET®**, Earth Best!
- Cast iron: **EN-GJS-500-7**, nodularity over **95%**!
- Flange Adaptors: for most common flange standards. **PN10/16/ANSI150** drilled

APPLICATION SCENARIO



Our Factory



Company Advantages

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06



I 工厂 : 生产车间, 研发中心.

II 工厂 CNC 加工中心, 数控车床, 数控铣床, 数控磨床.

III 工厂 检测设备, 检测设备.

IV 工厂 实验室 检测设备.

V 工厂 : GB, 工厂, 工厂, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609.

VI 工厂 : 工厂, 工厂, 工厂, 工厂, 工厂, 工厂, 工厂 / 工厂 / 工厂, 工厂.

Exhibition Photos



Our Certificates



□□□□ □□

Q : □□□ □□□□ □□ □□□ □□□□□?

A : □□□ □□, □□, □□, □□, Application System.

Q : □□□□□□ □□ □ □□□□?

A : □□□, □□□, □□□, □□□□□ □□. RKSfluid □□□□□□ □□ □□□ □□□□□. □□□ □□ □□□ □□□□□.

Q : □□□ □□ □□□ □□□□□?

A : RKSfluid□□ □□□ □□□ □□ □ □□□ 4 □□ □□□ □□□□□.

Q : □□ □□ □□

A : □□ □□□ 2 ~ 5 □ □□ □□□ □□□□□. □□□ □□□ □□ □□□ □ □□.

Q : MOQ

A : □□ □□□ □□ 1pc.

Q : □□ □□□ □□□□□?

□□ : □□ □□ 100 % □□ □□□, 2 □ □□. □□□ □□ □□□ □□□□□□□.

□□□ TUV, API, WRAS, CE, ISO □□□ □□□□□□.

□□□ DIN, ASME, BS EN, JIS, API, AWWA□ □□□□□□.

Q : □□□□ □□□ □□□□ □□□□□□□□□?

A : RKSfluid 20 70 R & D ,