

Features



Air Release valve

Size range:DN25–DN300

Pressure ratings:PN10 PN16

Body:Ductile Iron

Trim:SS304 SS316 etc

Connection:ARVS/KARS–BPT threaded, KARX–Flanged

Working temperature: $-10^{\circ}\text{C}\sim+80^{\circ}\text{C}$

□□:

1. □□ □□□□□ □□□ □□□□ □ □□ □ □□ □□ □□□□□ □□ □□□.
2. □□ □□□□ □□ □□□□ □ □□ □□ □□□ □□□ □□ □□□□ □□ □□□.
3. □□ □□□□□ Bottom □□ □□□ □□□□ □□ □□□ □□ □□□ □□ □□□□□. □□ □□□□ □□□□□ □□□□ □□ □□□□□.
4. □□ □□ □□□ □□□ □□ □□□□ □□, □□, □□ □□□ □□□□□. □□□ □□□ □□□□ □□□ □□□ □□□□ □□□□□.
5. comply bs en 1074-4



DN25-DN50



DN50-DN300

Our Factory



RKSfluid 1997 年 成立。 拥有 Foundry 车间， 配备 各种 规格 的 铸钢 件。 拥有 CNC 车间， 配备 各种 规格 的 铸钢 件。 拥有 各种 规格 的 铸钢 件。 拥有 各种 规格 的 铸钢 件。

Liaoning Province, 100% Chinese GB certified.

100% Chinese certified. 100% Chinese

certified with RK certification mark

mark, ISO, PED, CE, ADWO-2000, TUV

certified. ISO 9001, TS, API. Markings: GB, CE, ADWO-2000, TUV

certified, ISO 9001, TS, API. Markings: GB, CE, ADWO-2000, TUV

certified, ISO 9001, TS, API. Markings: GB, CE, ADWO-2000, TUV

certified, ISO 9001, TS, API. Markings: GB, CE, ADWO-2000, TUV

certified, ISO 9001, TS, API. Markings: GB, CE, ADWO-2000, TUV

"100% Chinese, 100% Certified" marking

markings. 100% Chinese certified!

100% Chinese certified: GB, CE, ADWO-2000, TUV

CNC certified, 100% Chinese, 100% certified, 100% certified

■ 100% Chinese, 100% certified, 100% certified, 100% certified

100% Chinese, 100% certified, 100% certified, 100% certified

✓ Markings: GB, CE, PED, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRA, KTW, API 6D, API609.

VI certified: GB, CE, PED, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRA, KTW, API 6D, API609.

Our Certificates



Exhibition Photos

