



## DESIGN FEATURES

### DURABLE

- No-pin connection, 1 pc blow-out proof stem
- DI/CI Nodularity over 95%

### ANTI-CORROSION

- Material: Epoxy powder:  , Earth Best!
- Coating Thickness: 200-250µm
- Spraying temp: over 200°C. Doesn't fade, even wipe with diethyl ether

### QUALITY STANDARD

- 100% quality test, follow DIN, ASTM, JIS, GB/T, ISO, BS EN, API
- ONLY ONE Manufacturer get CE certification up to DN1800
- 2 years warranty. 15000 times On-off test, 30000 times Destructive experiment







## APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport





# Our Factory



## Company Advantages

01

21 years of professional experience

03

Independent research and development team  
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06





I 工厂 : 工厂 车间, 工厂 办公室 车间.

II 工厂 CNC 车间 车间, 工厂 车间, 工厂 车间 车间 车间.

III 工厂 车间 车间 车间 车间 车间 车间 车间 车间.

IV 工厂 车间 车间 车间 车间 车间.

V 工厂 : GB, 工厂 车间, 工厂 车间, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609.

VI 工厂 车间 : 工厂 车间, 工厂 车间, 工厂 车间, 工厂 车间, 工厂 车间, 工厂 / 工厂 / 工厂 车间, 工厂 车间.

## Exhibition Photos



# Our Certificates



□□□□ □□

Q : □□□ □□□ □□ □□ □□□□□?

A : □□ □□, □□, □□, □□, □□ □□□.

Q : □□□□□□ □□ □ □ □□□□?

A : □□□, □□□□, □□□□, □□□□□□ □□. RKSfluid □□□□□□ □□ □□□ □□□□□□. □□□ □□□□□□, □□□□□ □□□□□□□□.

Q : □□ □□□ □□□□□?

A : RKSfluid□□ □□□ □□□ □□ □ □□□ 4 □□ □□□ □□□□□.

Q : □□ □□ □□

: □□ □□ □□ 2 ~ 5 □. □□□□ □□ □□□ □□.

Q : MOQ

: 1 □ □□ □□.

Q : □□□ □□ □□□?

: 100 % □□ □□□ □□ □□ 2 □ □□. □□□□ □□ □□□□□□□□.

□□□ TUV, API, WRAS, CE, ISO □□□ □□□□□□.

□□□ DIN, ASME, BS EN, JIS, API, AWWA□ □□□□□□.

Q : □□□ □□□□ □□□ □□□□ □□ □ □ □□□□?

A : RKSfluid 20 年 以来 以来 以来 70 年 以来 R & D 以来 以来 以来, 以来 以来 以来 以来 以来.