

000:00000000000

□□ □□ : DN50-DN2400 (NPS1 1 / 4-NPS96)

□□ : PN6 / PN10 / PN16 / PN25 (□□□ 150) / SABS 1123 1000/3 1600/3

□ : -29 °C ~ + 120 °C □ : □ □ : GGG40

 $\ \ \, \square\square:\mathsf{NR},\mathsf{NBR},\mathsf{EPDM},\mathsf{Viton},\square\square\square\mathsf{\ /\ PTFE}\;\square\square$

□ : SS316, SS304, SS420, SS416, 2CR13, SS410

00:000,70,000

| | | | | : API, DIN, ASME, ISO, ANSI, GB / T, BS EN, AWWA | | | : CE, WRAS, API, ISO9001 : 2015, OHSAS18001 : 2007

 $\ \ \, \square \ \, \square \ \, : \ \, \square, \ \, \square \square, \ \, \mathsf{HVAC}, \ \, \square \square, \ \, \square \square$



Resilient seat butterfly valve



Resilient seat butterfly valve



Resilient seat butterfly valve

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: DI+ Nylon

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange



Resilient seat butterfly valve



Double flange resilient seat butterfly valve



Short-neck butterfly valve for petroleum

PN10/PN16, ANSI 125LB/150LB,5K/10K	N10/PN16	ANSI	125LB/	150LB	,5K/10K
------------------------------------	----------	------	--------	-------	---------

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB, 5K/10K

Size:DN50-DN1000

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Flange

ANSI 125LB/150LB

Top Flange Standard:ISO5211

Size:2"-12"

Body: DI CI

Disc :Stainless Steel

Seat: EPDM, NBR, Viton

Connection:Wafer, Lug







BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size:DN50~DN600

Body:Ductile Iron

Disc:Ductile Iron+PTFE

Seat: PTFE

Connection: Wafer, Lug, Flange

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: Ductile Iron+PTFE

Seat: PTFE

Connection: Wafer, Lug, Flange

BSEN 1092, DIN 2501, ANSI, JIS, AS2129


Size: DN50~DN600

Body: WCB, CF8, CF8M

Disc: CF8+PTFE, CF8M+PTFE

Seat: PTFE

Connection: Wafer, Lug







BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB, CF8, CF8M

Disc: CF8+PTFE, CF8M+PTFE

Seat: PTFE

Connection: Wafer, Lug

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: CF8, CF8M

Seat: PTFE

Connection: Wafer, Lug, Flange

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB

Disc: CF8 +PTFE, CF8 +PFA

Seat: PTFE

Connection: Wafer, Lug, Flange

APPLICATION SCENARIO





















Food and drug













Exhibition Photos

































