

EN 1092-2 是 ISO 9000 認證標準 ISO 9001 的 ISO 9000 認證。 ISO 9000 是 ISO 9000, ISO, ISO 9000 認證。 ISO 9000 是 ISO 9000 認證 ISO 9000 認證。

ISO 9000: EN1092-2 / BS4504

ISO 9000: DIN 914 / DIN F5 / BS 5163

DESIGN FEATURES



Features



- Use AkzoNobel material.
- Super Anti-corrosion
- Epoxy powder coating 200-250um,
- Baking varnish over 200°C,

| NO. | | |
|-----|----------------|------------------|
| 1 | Body | GGG50 |
| 2 | Dise | GGG40+EPDM |
| 3 | Wedge nut | C48600 |
| 4 | Stem | SS431 |
| 5 | Bonnet | GT450-10 |
| 6 | Gasket | EPDM |
| 7 | Y-ring | EPDM85-90 |
| 8 | Fix ring | CuZn21Si3/C69300 |
| 9 | Thrust bearing | C69300 |
| 10 | Seal ring | EPDM70 |
| 11 | O ring | NBR |
| 12 | Retainer ring | POM |
| 13 | Bushing ring | POM |
| 14 | Gland | SS431 |
| 15 | Dustproof ring | EPDM85 |
| 16 | Dise core | GGG40 |
| 17 | Bolt | SS316 |





Free wedge nut, reduces the stem bending forces and at the same time enables it to be easily replaced.



The more compact new cap, reduces the water retention areas in order to reduce the risk of bacterial growth.



One piece stainless steel stem in for better resistance to axial load and to with stand higher operating torques.



Three locking tab for bayonet system prevents self-dismantling.



Dust guard integrating three O-ring shape, prohibiting the introduction of foreign bodies at the stem.



Male guiding system with composite sliding skate reduces the wear of the wedge against the body, allowing a smooth functionality and a longer life time of the valve.



Triple seal at the operating stem to ensure tightness with the test of time (2500 cycles).



New male composite sliding skate technology ensuring a low operating torque even under high differential pressure and preventing damage or corrosion generated by the friction.



APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



COMPANY FACTORY



COMPANY INFORMATION



I 0000: 0000 00, 00 0 0000 00.

II 00 CNC 000 00, 00 0000 0, 0000 00 00, 00 00 00 0 00.

III 000 00 00 00, 00 00 00 00 0000 000000.

VI 00 0000 0000 00000000 00000000.

V 00 00: GB, 00 00, 00 00, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609.

VI 00 00: 000000 00, 0 00, 000 00, 00 00, 000 00, 000 00, 00/00/00 000000, 00 00.

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06

COMPANY QUALIFICATION



COMPANY EXHIBITION



Partners



Delivery



Payment



F AQ

Q: ພວກເຮົາສາມາດຮັບການສົ່ງໄດ້ແນວໃດ?

A: ພວກເຮົາສາມາດສົ່ງໄດ້ທາງອາກາດ, ທາງທະເລ, ຫຼື ທາງບົນລະດົມ.

Q: ພວກເຮົາສາມາດຮັບການສົ່ງໄດ້ແນວໃດ?

A: ພວກເຮົາສາມາດສົ່ງໄດ້ທາງອາກາດ, ທາງທະເລ, ຫຼື ທາງບົນລະດົມ. RKSfluid ສາມາດສົ່ງໄດ້ທາງອາກາດ. ພວກເຮົາສາມາດສົ່ງໄດ້ທາງທະເລ.

Q: ພວກເຮົາສາມາດຮັບການສົ່ງໄດ້ແນວໃດ?

A: RKSfluid ສາມາດສົ່ງໄດ້ທາງອາກາດ ຫຼື ທາງທະເລ ທາງບົນລະດົມ.

Q: ພວກເຮົາສາມາດຮັບການສົ່ງໄດ້ແນວໃດ?

A: ພວກເຮົາສາມາດສົ່ງໄດ້ທາງອາກາດ ຫຼື ທາງທະເລ ທາງບົນລະດົມ. ພວກເຮົາສາມາດສົ່ງໄດ້ທາງອາກາດ.

Q: MOQ

A: ພວກເຮົາສາມາດສົ່ງໄດ້ 1pc.

Q: ພວກເຮົາສາມາດຮັບການສົ່ງໄດ້ແນວໃດ?

A: ພວກເຮົາສາມາດສົ່ງໄດ້ 100% ທາງອາກາດ, ທາງທະເລ, ຫຼື ທາງບົນລະດົມ.

ພວກເຮົາສາມາດສົ່ງໄດ້ TUV, API, WRAS, CE, ISO ທາງອາກາດ.

ພວກເຮົາສາມາດສົ່ງໄດ້ DIN, ASME, BS EN, JIS, API, AWWA ທາງອາກາດ.

Q: ພວກເຮົາສາມາດຮັບການສົ່ງໄດ້ແນວໃດ?

A: RKSfluid 20 ປີ ສາມາດສົ່ງໄດ້ 70 ປີ ທາງ R&D ທາງອາກາດ ຫຼື ທາງທະເລ, ຫຼື ທາງບົນລະດົມ.