



## DESIGN FEATURES

### DURABLE

- No-pin connection, 1 pc blow-out proof stem
- DI/CI Nodularity over 95%

### ANTI-CORROSION

- Material: Epoxy powder:  , Earth Best!
- Coating Thickness: 200-250µm
- Spraying temp: over 200°C. Doesn't fade, even wipe with diethyl ether

### QUALITY STANDARD

- 100% quality test, follow DIN, ASTM, JIS, GB/T, ISO, BS EN, API
- ONLY ONE Manufacturer get CE certification up to DN1800
- 2 years warranty. 15000 times On-off test, 30000 times Destructive experiment





## APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport





## Company Advantages

01

21 years of professional experience

03

Independent research and development team  
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06



I 工厂 : 工厂 工厂, 工厂 工厂 工厂.

工厂, 工厂 工厂 工厂, 工厂 工厂 工厂 工厂, 工厂 工厂 工厂 工厂 工厂 || 工厂 CNC.

III 工厂 工厂 工厂 工厂, 工厂 工厂 工厂 工厂 工厂 工厂.

IV 工厂 工厂, 工厂, 工厂 工厂 工厂 工厂 工厂 工厂.

V 工厂 工厂 : GB, 工厂 工厂, 工厂 工厂, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609.

VI 工厂 工厂 : 工厂 工厂 工厂 工厂, 工厂 工厂, 工厂 工厂, 工厂 工厂, 工厂 工厂 工厂 / 工厂 / 工厂 工厂 工厂, 工厂 工厂.

## Exhibition Photos



# Our Certificates



□□□□ □□

Q : □□ □□□□□□ □□, □□ □□ □□ □□□□□?

A : □□ '□□, □□, □□, □□, Application □□□.

Q : □□□ □□□□□□ □□ □ □ □□□□, □□□ □□□?

A : □□, □□, Hrdraulic, □□□□□ □□. RKSfluid □□□□□□ □□ □□□ □□□□. □□□ □□□□□ □□ □□□□□□□.

Q : □□□ □□ □□□ □□□□□?

A : RKSfluid□ □□□ □□□□□ □□□ □□ □ □□□ □ □□ □□□ □□□□□.

Q : □□ □□ □□

A : □□ □□□ 2 ~ 5 □□ □□□ □□□. □□□ □□□ □□□ □□.

Q : MOQ

A : □□ □□□ 1 □.

Q : □□□ □□ □□□ □□□□□?

A : □□□ □□ 100 % □□ □□□, 2 □ □□. □□□ □□□ □□□ □□□□□.

□□□ TUV, API, WRAS, CE, ISO □□□ □□□.

□□□ DIN, ASME, BS EN, JIS, API, AWWA□ □□□□□.

Q : □□□ □□□ □□□□ □□□ □□□□ □□ □ □□□?

A : RKSfluid 20 70 R & D ,