



## DESIGN FEATURES



### FEATURES

- ◆ Wafer type double flange butterfly valve
- ◆ Size: DN32–DN2400(NPS1 1/4–NPS96)
- ◆ Design Standard: API, DIN, ASME, ISO, ANSI, GB/T, BS EN, AWWA
- ◆ Connection: Wafer, Lug, U-Section
- ◆ Pressure: PN6–PN10–PN16(Class 150)
- ◆ Temperature:  $-29^{\circ}\text{C} \sim +120^{\circ}\text{C}$
- ◆ Valve seat: NBR, EPDM, Viton, Silicone Rubber
- ◆ Valve stem: SS316, SS304, SS420, SS416
- ◆ Application: Water, Power plant, HVAC, Food, Medicine, Desalination





Resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange



Resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: DI+ Nylon

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange



Resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange



Resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange



Double flange resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB, 5K/10K

Size:DN50-DN1000

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Flange



Short-neck butterfly valve for petroleum

ANSI 125LB/150LB

Top Flange Standard:ISO5211

Size:2"-12"

Body: DI CI

Disc :Stainless Steel

Seat : EPDM, NBR, Viton

Connection:Wafer, Lug



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: Ductile Iron+PTFE

Seat: PTFE

Connection: Wafer, Lug, Flange



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: Ductile Iron+PTFE

Seat: PTFE

Connection: Wafer, Lug, Flange



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB, CF8, CF8M

Disc: CF8+PTFE, CF8M+PTFE

Seat: PTFE

Connection: Wafer, Lug



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB, CF8, CF8M

Disc: CF8+PTFE, CF8M+PTFE

Seat: PTFE

Connection: Wafer, Lug



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: CF8, CF8M

Seat: PTFE

Connection: Wafer, Lug, Flange



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB

Disc: CF8 +PTFE, CF8 +PFA

Seat: PTFE

Connection: Wafer, Lug, Flange

## APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport





# Our Factory



RKSfluid 1997 年 成立。 公司 拥有  
 先进 的 生产设备 和 技术 人员。 公司  
 采用 CNC 加工 技术， 生产 各种 规格 的 阀门。  
 公司 拥有 完善 的 质量管理体系， 确保 产品 质量。  
 公司 产品 广泛应用于 石油、 化工、 电力、 冶金 等行业。  
 公司 产品 符合 国际 标准 GB 标准 和 欧洲 标准。

මම මම මම මම මම. මම මමමම මම  
මම මමම ම මම මම ම RKS මම මමම මම  
මම, මම, මමම මම මම. මම මම මමම මමම. මම මම මම මම  
COP : CE ම ADWO-2000 ම TUV ම ම GB, ISO, ම ම ම ම, ISO9001, TS, API. මම මම : මම, ම ම මමම මමම ම ම, ම ම ම මම ම. ම ම, ම ම ම. මම  
මම : ම ම, ම, මම, ම, ම ම, මමම ම ම, මම මම, ම ම. මම මම, මම මම මමමම මම මමමම.  
"ම ම ම, මම ම ම මමම ම" ම මම  
ම ම ම. ම මම මම ම මමමම!  
ම ම ම : ම ම ම ම, ම ම ම ම ම ම.

ම ම CNC මම ම, ම ම ම, ම ම, ම ම ම ම ම ම.

ම මම ම ම මම ම ම ම ම ම ම මමමම.

☒ මම මම ම මම (Houston) ම ම ම මම මමමමම.

◆ ම ම : GB, ම ම, ම ම, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609.

VI ම ම : ම මම ම, ම ම, මම ම, ම ම, මම ම, මම ම, ම / ම / ම මමමම, ම ම ම.



## Our Certificates



## Exhibition Photos

