



RKSfluid®

A key Valve in Flow Control

Butterfly Valve

Ball Valve

Gate Valve

Globe Valve

Check Valve

Pipe Fittings



该阀门适用于各种工业管道系统，用于控制流体的流动。该阀门具有坚固的结构和可靠的密封性能，适用于高温、高压的工作环境。该阀门的额定工作压力为 10 MPa，额定温度为 $\leq 80^{\circ}\text{C}$ 。



TILTING CHECK VALVE (BUTTERFLY CHECK VALVE)
DN100-DN1200,PN10/16/25

Features

- Double flange tilting check valve with Hydraulic damper
- Size range DN100–1200mm
- Standard–ISO/ BS/DIN /AWWA/API
- Tests standard–BS EN 12266–1
- Body–Ductile Iron/Cast Iron/Stainless Steel/WCB
- Disc–Ductile iron /Cast Iron/Stainless Steel /WCB

- Body Ring–SS420/SS304/SS316
- Retaining Ring–SS420/SS304 /SS316
- Disc Ring–EPDM
- Shaft–420/S5431/SS316
- Fusion bonded epoxy coating– Min 300 Microns

SPECIFICATION

Nominal pressure (MPa)		1.6
Testing pressure(MPa)	Seal	2.4
	Shell	1.76
Working pressure (MPa)		1.6
Suitable temperature (°c)		<80°c
Suitable medium		Water

TECHNICAL REQUIREMENT

- 1.Face to face standard: EN 558 Series 14.
- 2.Flanges standard: BS EN1092-2:1997 PN16.
- 3.Tests standard: BS EN12266-1:2003 Part 1 Rate A .

MATERIALS OF CONSTRUCTION

No.	Part Name
1	Body
2	Shaft bushes
3	Shaft
4	Cover
5	Retainer ring
6	Disc sealing ring
7	Body sealing ring
8	Disc
9	Weight

Our Factory



Company Advantages

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06



□ □ □ □ : □ □ □ □ □ □, □ □ □ □ □ □ □ □.

□ □ □ CNC □ □ □ □ □ □, □ □ □ □ □, □ □ □ □ □ □ □ □, □ □ □ □ □ □ □ □ □.

□ □.

❏ □ □ □ □ □ □ □ □ □ □ (Houston) □ □ □ □ □ □ □ □ □ □ □ □ □ □.

◆ □ □ □ □ : GB, □ □ □ □, □ □ □ □, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609.

VI □ □ □ □ : □ □ □ □ □ □, □ □ □ □, □ □ □ □, □ □ □ □, □ □ □ □ □ □, □ □ □ □ □ □, □ □ / □ □ / □ □ □ □ □ □ □ □, □ □ □ □.

Exhibition Photos



Our Certificates



□□□□ □□

Q : □□□□ □□□□ □□ □□□ □□□□□?

A : □□□ □□, □□, □□, □□, □□ □□□.

Q : □□□□□□ □□ □ □ □□□□?

A : □□□, □□, □□, □□□□□ □□. RKSfluid □□□□□□ □□ □□□ □□□□□. □□□ □□□□□, □□ □□□□□□.

Q : □□□ □□ □□□ □□□□□?

A : RKSfluid□□ □□□ □□□ □□ □ □□□ 4 □□ □□□ □□□□.

Q : □□ □□ □□

A : □□□□ □□□ 2 ~ 5 □ (2 ~ 5 □)□ □□□□. □□□□ □□□ □□ □□□ □□ □ □□.

Q : MOQ.

A : □□ □□□ □□ 1pc.

Q : □□ □□□ □□□□□?

A : □□ □□ 100 % □□ □□□, 2 □ □□. □□□□ □□□□ □□□□□.

□□□ TUV, API, WRAS, CE, ISO □□□ □□□□□.

□□, DIN, ASME, BS EN, JIS, API, AWWA.

Q : RKSfluid 20 70 R & D

A : RKSfluid 20 70 R & D