

DESIGN FEATURES



- 1.Elastic stainless steel sealing ring,"0"leakage
- 2.Fireproof structural design,blow-out proof stems
- 3.Auto welding plasma powder surfacing valve seat
- 4.Hollow design, reduces flow resistance
- 5.Interchangeable DSS entity seal / multiple-piece
- 6.stainless and graphite seal
- 7.ISO5211 Mounting platform,simple connection



APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



COMPANY INFORMATION



i 0000 00 : 00 00 00, 00 0 00 00 00.

CNC 00 00, 00 00 0, 0000 00 00, 00 00 00 0 00.

■ 00 00 00 000 000 000000 000 00 00 00.

000 0000 000 0000 00 00 000 000000.

v 00 00 : GB, 00 00, 00 00, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRA, KTW, API 6D, API609.

VI 00 0000 : 00 00, 0 00, 000 00, 00 00, 000 00, 000 00, 00 / 00 / 00 00000, 00 00.

COMPANY QUALIFICATION



COMPANY EXHIBITION



□□□□ □□

Q : □□□ □□□ □□ □□ □□□□□□?

A : □□□ □□, □□, □□, □□, □□ □□□.

Q : 閥の種類はどれですか？

A : 球閥, 蝶形閥, hydraulic, 電磁弁など.RKSfluid には様々な種類があります。また、材質もステンレス鋼や銅合金などがあります。

Q : どのサイズがありますか？

A : RKSfluidは口径 1/2 から 4 インチまでのサイズがあります。

Q : どの材質がありますか？

A : 球閥は 2 ~ 5 MPa の圧力に対応しています。材質はステンレス鋼や銅合金などがあります。

Q : MOQ

A : 球閥は 1pc からです。

Q : どの規格がありますか？

A : 球閥は 100% 検査済みで、2 年保証です。また、ISO 9001 認証済みです。

TUV, API, WRA, CE, ISO 9001 認証済みです。

また、DIN, ASME, BS EN, JIS, API, AWWA などの規格にも対応しています。

Q : どのサイズがありますか？

A : RKSfluid は口径 20 から 70 mm のサイズがあり、R & D 部門も対応しています。また、材質もステンレス鋼や銅合金などがあります。