



RKSfluid®

A key Valve in Flow Control



Butterfly Valve



Ball Valve



Gate Valve



Globe Valve



Check Valve



Pipe Fittings

Product Description



Super Anti-corrosion
Epoxy powder coating **200-250µm**,
baking varnish over **200°C**,
use  material.



Free wedge nut, **reduces the stem bending forces** and at the same time enables it to be easily replaced.



The more compact new cap, reduces the water retention areas in order to **reduce the risk of bacterial growth**.



One piece stainless steel stem in for **better resistance to axial load and to with stand higher operating torques**.



Three locking tab for bayonet system prevents self-dismantling.



Dust guard integrating three O-ring shape, **prohibiting the introduction of foreign bodies** at the stem.



Male guiding system with composite sliding skate reduces the wear of the wedge against the body, allowing a smooth functionality and a longer life time of the valve.



Triple seal at the operating stem to ensure tightness with the test of time (2500 cycles).



New male composite sliding skate technology ensuring a low operating torque even under high differential pressure and preventing damage or corrosion generated by the friction.

Design standard

Design standard	BS EN 1171 ANSI
Flange	GB/T 17241.6-2008、 DIN 2633-1975、 BS EN1902-2
Face to face	GB/T 12221-2005、 ISO 5752-1988、 BS EN558-1(F4、 F5)
Test standard	EN12266

Specification

Size	DN50-900
Pressure	PN10 PN16 class150
Medium	Water
Temperature	0°C~90°C

PRODUCT DISPLAY



SHIPPING PACKAGING



COMPANY INFORMATION



□ □ □ □ : □ □ □ □, □ □ □ □ □ □ □ □ □ □.

□ □ □ CNC □ □ □ □, □ □ □ □ □, □ □ □ □ □ □ □ □, □ □ □ □ □ □ □ □.

□ □□□ □□ □□ □□ □□ □□ □□ □□ □□□□.

□ □□□ □□□ □ □□□ (Houston) □ □□ □□ □□□□□□.

◆ □□ □□ : GB, □□ □□, □□ □□, CE TUV, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609.

□□ □□ : □□ □□□ □□, □ □□, □□□ □□, □□ □□, □□□ □□, □□ □□, □□ / □□□ / □□ □□□□□, □□ □□.



EXHIBITION



COMPANY INFORMATION



□□□□ □□

Q : □□□□ □□□□ □□ □□ □□□□□?

A : □□ □□, □□, □□, □□ □□□□, □□□.

Q : □□□□□□ □□ □ □ □□□□. □□□ □□□ □□□□?

A : □□□, □□, □□, □□□□□ □□. RKSfluid □□□□□□ □□ □□□ □□□□□□. □□□ □□□□□□.

Q : □□□ □□ □□□ □□□□□?

A : RKSfluid□□ □ □□ □□□ □□□ □□ □ □ □□□□.

D : □□ □□ □□

A : □□ □□□ 2 ~ 5 □□ □□□ □□□ □□□□□. □□□ □□□ □□ □□□ □□ □□.

D : MOQ.

A : □□ □□□ □□ 1pc.

Q : 如何 测试 密封性?

A : 如何 测试 100 % 密封 性能, 2 个 测试. 密封性 测试 密封性.

如何 TUV, API, WRAS, CE, ISO 如何 密封性.

DIN, ASME, BS EN, JIS, API, AWWA 如何 密封性.

Q : 如何 测试 密封 性能 如何 测试 密封性?

A : RKSfluid 如何 测试 密封 性能 70 个 测试 密封 性能 如何 测试, 如何 测试 密封 性能 密封性.