RKSfluid®
A key Valve in Flow Control
Butterfly Valve
Ball Valve
Gate Valve
Globe Valve
Check Valve
Pipe Fittings

Product Description

Super Anti-corrosion

Epoxy powder coating 200-250μm,

baking varnish over 200℃,

use AkzoNobel material.

Free wedge nut, reduces the stem bending forces and at the same time enables it to be easily replaced.

The more compact new cap, reduces the water retention areas in order to reduce the risk of bacterial growth.

One piece stainless steel stem in for better resistance to axial load and to with stand higher operating torques.

Three locking tab for bayonet system prevents self-dismantling.

Dust guard integrating three O-ring shape, prohibiting the introduction of foreign bodies at the stem.

Male guiding system with composite sliding skate reduces the wear of the wedge against the body, allowing a smooth functionality and a longer life time of the valve.

Triple seal at the operating stem to ensure tightness with the test of time (2500 cycles).

New male composite sliding skate technology ensuring a low operating torque even under high differential pressure and preventing damage or corrosion generated by the friction.

Design standard

Design standard	BS EN 1171 ANSI
Flange	GB/T 17241.6-2008、 DIN 2633-1975、 BS EN1902-2
Face to face	GB/T 12221-2005、 ISO 5752-1988、 BS EN558-1(F4、F5)
Test standard	EN12266

Specification

Size	DN50-900
Pressure	PN10 PN16 class150
Medium	Water
Temperature	0℃~90℃

PRODUCT DISPLAY

SHIPPING PACKAGING

COMPANY INFORMATION

□ □□ □□ : □□ □□, □□ □ □□ □□ □□□□□□ □□.

□ □□ CNC □□□ □□, □□ □□ □, □□□ □ □□ □□, □□ □□ □□ □ □□.

□ □□□ □□ □□ □□□ □□ □□ □□ □□ □□□ □□□□□.

□ □□□ □□□ □ □□□ (Houston)□ □□ □□ □□□ □□□□□□.

◈ □□ □□ : GB, □□ □□, □□ □□, CE TUV, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609.

□□ □□ : □□ □□□ □□, □ □□, □□□ □□, □□ □□, □□□ □□, □□ □□, □□ / □□□ / □□ □□□□□, □□ □□.

EXHIBITION

RKSfluid

RKSfluid®

RKSfluid

RKSfluid®

RKSfluid

RKSfluid

RKSfluid®

COMPANY INFORMATION

□□□□ □□

Q : □□□□ □□□□ □□ □□□ □□□□□?
A : □□ □□, □□, □□, □□ □□□, □□□.

Q : □□□□□□ □□ □ □ □□□□. □□□ □□□ □□□□?
A : □□□, □□, □□, □□□□□ □□. RKSfluid □□□□□□ □□ □□□ □□□□□. □□□ □□□□□.

Q : □□□ □□ □□□ □□□□□?
A : RKSfluid□□ □ □□ □□□ □□□ □□□ □□ □ □ □□□□.

D : □□ □□ □□
A : □□ □□□ 2 ~ 5 □□ □□□ □□□ □□□□. □□□ □□□ □□ □□□ □□ □□.

D : MOQ.
A : □□ □□□ □□ 1pc.

Q : □□ □□□ □□□□□?
A : □□ □□ 100 % □□ □□□, 2 □ □□. □□□□ □□□ □□□□□□.
□□□ TUV, API, WRAS, CE, ISO □□□ □□□□□□.
DIN, ASME, BS EN, JIS, API, AWWA□ □□□□ □□.

Q : □□□□ □□□ □□ □□□□ □□ □ □ □□□□?
A : RKSfluid□ 20 □□ □□□ 70 □ □□□ □□ □□ □□□□□ □□ □□, □□ □□ □ □□ □□□□ □□□□□.