



DESIGN FEATURES

DURABLE

- No-pin connection, 1 pc blow-out proof stem
- DI/CI Nodularity over 95%

ANTI-CORROSION

- Material: Epoxy powder:  , Earth Best!
- Coating Thickness: 200-250µm
- Spraying temp: over 200°C. Doesn't fade, even wipe with diethyl ether

QUALITY STANDARD

- 100% quality test, follow DIN, ASTM, JIS, GB/T, ISO, BS EN, API
- ONLY ONE Manufacturer get CE certification up to DN1800
- 2 years warranty. 15000 times On-off test, 30000 times Destructive experiment





APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport





VI 00 00 : 00 0 00, 0 00, 000 00, 00 00, 000 00, 000 00, 00 / 00 / 00 00000, 00 00.

Exhibition Photos



Our Certificates



Q : 0000 0000 00 000 000000?

A : 0000 00, 00, 00, 00, 00 0000.

Q : 0000000 00 0 0 00000?

A : 0000, 00, 00, 000000 00. RKSfluid 0000000 00 0000 000000. 0000 000000, 00 00000000.

Q : 0000 00 0000 000000?

A : RKSfluid000 0000 0000 00 0 0000 4 00 0000 00000.

Q : 00 00 00

A : 00000 0000 2 ~ 5 0 (2 ~ 5 0)0 00000. 0000 0000 00 0000 00 0 00.

Q : MOQ.

A : 00 0000 00 1pc.

Q : 00 0000 000000?

A : 00 00 100 % 00 0000, 2 0 00. 00000 00000 000000.

0000 TUV, API, WRAS, CE, ISO 0000 0000000.

00, DIN, ASME, BS EN, JIS, API, AWWA.

Q : 00000 0000 00000 00 0 0 00000?

A : RKSfluid 0000 20 0 0000 70 0 0000 R & D 0000000 00 00, 00 00 0 00 0000 000000.