

Features



Air Release valve

Size range:DN25–DN300

Pressure ratings:PN10 PN16

Body:Ductile Iron

Trim:SS304 SS316 etc

Connection:ARVS/KARS–BPT threaded, KARX–Flanged

Working temperature: $-10^{\circ}\text{C}\sim+80^{\circ}\text{C}$

□□:

1. □□□ □□□□ □□□ □□ □□□, □□□□ □ □□ □ □□ □□ □□□ □□ □□ □□□.
2. □ □□ □□ □□□ □□□ □□□□ □□□□ □□□ □□□ □□□.
3. □□ □□□□□ □□□ □□ □□ □ □□ □□ □□□ □□□ □□□ □□ □□□.
4. □□ □□ □□□ □□, □□, □□□ □□□ □□□ □□□ Float.smooth □□□□ □□ □□□ □□□□□, □□□ □□□ □□□□ □□□□□.
5. BS EN 1074-4□ □□



DN25-DN50



DN50-DN300

Our Factory



RKSfluid 1997 年 成立。 拥有 先进
 设备， 采用 国际 标准 生产。 拥有
 先进 CNC 加工设备， 能够 生产 各种
 规格 阀门， 满足 客户 需求。
 产品 广泛应用于 石油、 化工、 电力、
 冶金 等行业。 欢迎广大 客户 垂询。

GB
RKS
COP : CE ADWO-2000 TUV GB, ISO, ISO9001, TS, API.
API

CNC

(Houston)

GB, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609.

VI

Our Certificates



Exhibition Photos

