□□□ : □□□□ □□□□ □□ □□
□□ □□ : DN50-DN2400 (NPS1 1 / 4-NPS96)
□□ : PN6 / PN10 / PN16 / PN25 (□□□ 150) / SABS 1123 1000/3 1600/3
□□ : -29 ℃ ~ + 120 ℃
□□ : □□ □ : GGG40
□□ : NR, NBR, EPDM, Viton, □□□ / PTFE □□
□□□ / □□ : □□□ □□ □□ □, SS316, SS304, □□□□□ □□ □□□□, □□
□□ : SS316, SS304, SS420, SS416, 2CR13, SS410
□□ : □□□, 7 □, □□□
□□□ □□ : API, DIN, ASME, ISO, ANSI, GB / T, BS EN, AWWA
□□□ : CE, WRAS, API, ISO9001 : 2015, OHSAS18001 : 2007
□□ □□ : □, □□□, HVAC, □□, □□, □□

Resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB,5K/10K
Size:DN25-DN2400
Body:DI CI
Disc: Stainless steel
Seat :EPDM, NBR, Viton
Connection: Wafer, Lug, Flange

Resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB,5K/10K
Size:DN25-DN2400
Body:DI CI
Disc: DI+ Nylon
Seat :EPDM, NBR, Viton
Connection: Wafer, Lug, Flange

Resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB,5K/10K
Size:DN25-DN2400
Body:DI CI
Disc: Stainless steel
Seat :EPDM, NBR, Viton
Connection: Wafer, Lug, Flange

Resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB,5K/10K
Size:DN25-DN2400
Body:DI CI
Disc: Stainless steel
Seat :EPDM, NBR, Viton
Connection: Wafer, Lug, Flange

Double flange resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB, 5K/10K
Size:DN50-DN1000
Body:DI CI
Disc: Stainless steel
Seat :EPDM, NBR, Viton
Connection: Flange

Short-neck butterfly valve for petroleum

ANSI 125LB/150LB
Top Flange Standard:ISO5211
Size:2"-12"
Body: DI CI
Disc :Stainless Steel
Seat : EPDM, NBR, Viton
Connection:Wafer, Lug

PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129
Size:DN50~DN600
Body:Ductile Iron
Disc:Ductile Iron+PTFE
Seat: PTFE
Connection: Wafer, Lug, Flange

PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129
Size: DN50~DN600
Body: Ductile Iron
Disc: Ductile Iron+PTFE
Seat: PTFE
Connection: Wafer, Lug, Flange

PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129
Size: DN50~DN600
Body: WCB, CF8, CF8M
Disc: CF8+PTFE, CF8M+PTFE
Seat: PTFE
Connection: Wafer, Lug

PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129
Size: DN50~DN600
Body: WCB, CF8, CF8M
Disc: CF8+PTFE, CF8M+PTFE
Seat: PTFE
Connection: Wafer, Lug

PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129
Size: DN50~DN600
Body: Ductile Iron
Disc: CF8 , CF8M
Seat: PTFE
Connection: Wafer, Lug, Flange

PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129
Size: DN50~DN600
Body: WCB
Disc: CF8 +PTFE, CF8 +PFA
Seat: PTFE
Connection: Wafer, Lug, Flange

APPLICATION SCENARIO

RKS Fluid□ 1997 □□ □□□□□□□. □□□ □□□□ □ □□, □□ □□ □□ □ □□ □□ □□ □□□□□ □□ □□□□□ □. □□ □□□□ CNC □□□ □□, □□ □□ □, □□ □□□□ □□ □□, □□ □□ □ □□ □□□ □□□□. □□□ □□□, □□ □ □□ □□ □□□□□□. □□□ □□□ □□□ □□□ Liaoning □□□ □□ □□□ □□□□ □□□□, □□ □□ □□ □□□ □ □ GB□□□ □□ □□ □□ □□ □□□ □□□□□. □□ □□□ □□□ □□□ □□□□□ □□, □□□, □□□□□□ RKS □□ □ □□ □□□ □□□□ □□. □□□□□ □□□□ □□□□. □□□ □□ □□□ □□ : CE □ ADWO-2000, ISO9001, TS, API □ TUV□ □□ □ GB, ISO, □□ □ □□ □□. □□□ □□ : □□ □ □□, □□□ □ □□□□□ □□□□ □□□□ □ □□□□, □□ □□ □ □□□ □□. □□ □□, □□ □□ □□. □□ □ □□ : □□ □□, □□, □□□, □□, □□ □□, □□□□ □□□, □□□ □□□, □□ □□. □□□□ □□□ □□□ □□□ □□ □□□□ "□□ □ □□, □□□ □□ □ □□□□ □□"□ □□□ □ □□ □□□ □□□ □□ □□□□□□. □□ □□□ □□□ □□ □□□□□!

Exhibition Photos

Our Certificates