RKSfluid®
A key Valve in Flow Control
Butterfly Valve
Ball Valve
Gate Valve
Globe Valve
Check Valve
Pipe Fittings

□□ □□ □□□ □□□ ater □□ □ □□□ □□□ □□□□□ □□□□. □□ □□□□□ □□ □□□□□ □□ □□□ □□ □□□□. □□□ □□□ □□ □□□□ □□ □ □ □ □□□. □□□ temperature≤80 ° C

TLV TILTING CHECK VALVE (BUTTERFLY CHECK VALVE
DN100-DN1200,PN10/16/25

Features

- Double flange tilting check valve with Hydraulic damper
- Size range DN100-1200mm
- Standard-ISO/ BS/DIN /AWWA/API
- Tests standard-BS EN 12266-1
- Body-Ductile Iron/Cast Iron/Stainless Steel/WCB
- Disc-Ductile tron /Cast Iron/Stainless Steel /WCB

- Body Ring-SS420/SS304/SS316
- Retaining Ring-SS420/SS304 /SS316
- Disc Ring-EPDM
- Shaft-420/S5431/SS316
- Fusion bonded epoxy coating- Min 300 Microns

SPECIFICATION		
Nominal pressure (MPa)		1.6
Testing pressure(MPa)	Seal	2.4
	Shell	1.76
Working pressure (MPa)		1.6
Suitable temperature (°c)		<80°c
Suitable medium		Water

TECHNICAL REQUIREMENT

1.Face to face standard: EN 558 Series 14.
2.Flanges standard: BS EN1092-2:1997 PN16.
3.Tests standard: BS EN12266-1:2003 Part 1 Rate A .

MATERIALS OF CONSTRUCTION

No.	Part Name
1	Body
2	Shaft bushes
3	Shaft
4	Cover
5	Retainer ring
6	Disc sealing ring
7	Body sealing ring
8	Disc
9	Weight

Our Factory

Company Advantages

01 21 years of professional experience

02 4 factories

03 Independent research and development team
28 top senior professional researchers

04 2 professional testing centers

05 100% high level ex-factory inspection

06 High quality imported materials

07 2 years quality assurance, repair and replacement

I □□ □□ : □□ □□ □□, □□ □ □□ □□ □□.

□□, □□ □□□ □□, □□ □□□ □□ □□, □□ □□ □□ □ □□ □□ Ⅱ □□ CNC.

Ⅲ □□□ □□ □□ □□, □□ □□ □□ □□□ □□□ □□□□□.

Ⅳ □□□ □□, □□□, □□□□□□ □□ □□ □□□ □□□□.

V □□ □□ : GB, □□□ □□, □□ □□, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609.

VI □□ □□ : □□ □ □□□ □□, □□□ □□, □□ □□, □□□ □□, □□□ □□ □□ / □□ / □□ □□□□□, □□ □□.

Exhibition Photos

□□□□ □□

Q : □□ □□□□□□□□ □□, □□ □□ □□□ □□□□□?
A : □□ '□□, □□, □□, □□, Appllication □□□.

Q : □□□ □□□□□□ □□ □ □ □□□□, □□□ □□□?
A : □□, □□, Hrdraulic, □□□□□ □□. RKSfluid □□□□□□ □□ □□□ □□□□. □□□ □□□□□ □□ □□□□□□.

Q : □□□ □□ □□□ □□□□□?
A : RKSfluid□ □□□ □□□□□ □□□ □□ □ □□□ □ □□ □□□ □□□□□.

Q : □□ □□ □□
A□ : □□ □□□ 2 ~ 5 □□ □□□ □□□. □□□ □□□ □□□ □□.

Q : MOQ
A : □□ □□□ 1 □.

Q : □□□ □□ □□□ □□□□□?
A : □□□ □□ 100 % □□ □□□, 2 □ □□. □□□ □□□ □□□ □□□□□.
□□□ TUV, API, WRAS, CE, ISO □□□ □□□.
□□ DIN, ASME, BS EN, JIS, API, AWWA□ □□□□□.

Q : □□□ □□□ □□□□ □□□ □□□□ □□ □ □□□?
A : RKSfluid □□□ 20 □ □□□ 70 □ □□□ R & D □□□□□ □□ □□, □□ □□ □ □□ □□□ □□□□□.