



- Better sealing effect, prevent leakage
- Easier replace the filter bag, lower operating cost
- Adjustable installation height to meet specific application occasions
- Large effective filtration area and higher filtration efficiency
- Longer filter bag service life
- Reasonable structure, more stable and reliable filtration
- China GB-150, International ASME, CE Pressure Standards



- Filter different chemical **acid** and **alkali** liquids
- No seam, no dead angle, precise specification
- Smooth surface, no groove, no dead angle, easy to clean
- Can withstand **high temperature** and **high pressure**
- High quality, high efficiency, economical & practical



- Suitable for high capacity & large flow filtration
- Provided 3 ~ 24 bags design structure
- Equipped with standard size flange
- Flow from 120 to 960 cubic/hours
- Excellent welding quality, safe and reliable

## Our Factory





## Exhibition Photos



## Our Certificates



□□□□ □□

Q1 : □□□ □□□ □□□ □□?

A1 : □□ □□□□ □□, □□, □□□□ □□□□□□.

Q2 : □□ □□?

A2 : □□□ □□ 5-10 □, □□□ □□ 15-90 □ □□ □□□.

Q3 : □□ □□?

A3 : T / T 30 % □□, □□ □□ □□ □□ □ □□□. □□ □□□□□□.

Q4 : □□□ MOQ? □□ □□□ □ □ □□□□?

A4 : □□□ 1 □ □□, □□□ □□□ □□□□□□. □□□ □□ □□.

Q5 : □□ □□? □□□ □□□ □□ □□□ □□ □□□□□□?

A5 : □□□□□□, 100 % □□. □□□ □□□ □□□ □□ □□□ □ □□□□□.

Q6 : □□□ □□ □□ □□□ □□□ □□□ □□ □ □□□□□□?

A6 : □□, □□□ □□ □□□ □□, □□□ □□□□□□ □□□ □□, □□ □□□ □□ □□.

Q7 : □□□ □□ □ □□□ □ □□?

A7 : □□ 1 □. □□□ □□ □□□ □□, □□ □□□□□□ □□□□□.