

Product Display

This series tilting check valves are suitable to be used at the exit of the pump whose medium is water. It is used to prevent or reduce medium back from water hammer. So it can protect the pipeline system. Suitable temperature $\leq 80^{\circ}C$

TLV TILTING CHECK VALVE (BUTTERFLY CHECK VALVE) DN100- DN1200, PN10 / 16/25

Features

- Double Flange Tilting Check Valve With Hydraulic damper
- Size range DN100-1200mm
- Standard-ISO/BS/ DIN /AWWA/API
- Tests Standard BS EN 12266-1
- Body-Ductile Iron / Cast Iron / Stainless Steel / WCB
- Disc-Ductile tron / Cast Iron / Stainless Steel / WCB

	SPECIFI	CATION	
N	ominal pressure (MPa)	1	1.6
-	Testing pressure(MPa)	Seal	2.4
1		Shell	1.76
Working pressure (MPa)			1.6
Suitable temperature (°c)			<80°c
S	Suitable medium		Water
	1		

TECHNICAL REQUIREMENT

1.Face to face standard: EN 558 Series 14.

- 2.Flanges standard: BS EN1092-2:1997 PN16.
- 3.Tests standard: BS EN12266-1:2003 Part 1 Rate A.

- Body Ring -SS420/SS304/SS316
- Retaining Ring SS420 / SS304 /SS316
- Disc Ring EPDM
- Shaft -SS420/SS431/SS316
- Fusion bonded epoxy coating- Min 300 Microns

No.	Part Name	
NO.	Fait Name	
1	Body	
2	Shaft bushes	
3	Shaft	
4	Cover	
5	Retainer ring	
6	Disc sealing ring	
7	Body sealing ring	
8	Disc	
9	Weight	

Series: Titling Butterfly type Check Valve Port Size: DN100-DN1800 Pressure: PN6, PN10, PN16(Class 150) Temperature: -29°C ~ +120°C Body: Ductile Iron: GGG40 Seat: NR, NBR, EPDM, Viton, Silicone Rubber Disc/Trim: Epoxy Coated Ductile Iron,SS316,SS304,Duplex Stainless Steel,Al Bronze Stem: SS316,SS304,SS420,SS416 Design Standard: API,DIN,ASME,ISO,ANSI,GB/T,BS EN,AWWA Certificate: CE ,WRAS,API,ISO9001:2015,OHSAS18001:2007 Application: water,power plant,HVAC,Food,Medicine,Desalinat

APPLICATION SCENARIO

















PTFE lined butterfly valve



Triple offset butterfly valve



Resilient seat butterfly valve



Ball valve



Double offset butterfly valve



Pipe fittings

Our Factory



I Business area: fluid control products, technology and environmental protection products.

Il Advanced CNC machining centers, professional process cells, wide-range welding equipment, automatic assembly lines and coating.

III China's standard reference unit, to participate in the development of relevant valve industry standards.

IV We have set up a research and development center in Houston, Texas, in the United States.

V Product Standard: GB, German Standard, American Standard, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609.

VI Main production: butterfly valve, ball valve, gate valve, check valve, globe valves, pipe fittings, manual / pneumatic / electric actuator, valve parts.

21 years of professional experience

03

05

07

Independent research and development team 28 top senior professional researchers

100% high level ex-factory inspection

2 years quality assurance, repair and replacement

Company Advantages

50

04

06

4 factories

2 professional testing centers

High quality imported materials

Exhibition Photos





FAQ

Q: If I need quotation, what informations do we need?

A: Valves' materials, Temperature, Pressure, Medium, Appllication System.

Q: Can you provide actuators, what you have?

A: Pneumatic, Electric, Hrdraulic, Solenoid Valves. RKSfluid actuators adopt USA technology. Which you need, just tell us.

Q: What's your productive capacity?

A: RKSfluid has four plants that can provide the products you need.

Q: Production lead time

A: Normal products have stock in 2~5 working days. Customized base on your need.

Q: MOQ

A: 1pc for all products.

Q: How about the quality assurance?

A: 100% quality test before delivery, 2 years warranty. Ensure your system working safety. We got TUV, API, WRAS, CE, ISO certification. Standard conform to DIN, ASME, BS EN, JIS, API, AWWA.

Q: How could you provide quality service to our customers?

A: RKSfluid own 20 years experiences and more than 70 R&D engineers provide technical support, model selection and installation guidance for you.