



RKsfluid®

A key Valve in Flow Control



Butterfly Valve



Ball Valve



Gate Valve



Globe Valve



Check Valve



Pipe Fittings

Product Description



Super Anti-corrosion
Epoxy powder coating **200-250µm**,
baking varnish over **200°C**,
use  material.



Free wedge nut, **reduces the stem bending forces** and at the same time enables it to be easily replaced.



The more compact new cap, reduces the water retention areas in order to **reduce the risk of bacterial growth**.



One piece stainless steel stem in for **better resistance to axial load and to with stand higher operating torques**.



Three locking tab for bayonet system prevents self-dismantling.



Dust guard integrating three O-ring shape, **prohibiting the introduction of foreign** bodies at the stem.



Male guiding system with composite sliding skate reduces the wear of the wedge against the body, allowing a smooth functionality and a longer life time of the valve.



Triple seal at the operating stem to ensure tightness with the test of time (2500 cycles).



New male composite sliding skate technology ensuring a low operating torque even under high differential pressure and preventing damage or corrosion generated by the friction.

[Related products: TLG series Metal Seal No-](#)

rising

valve

DESIGN FEATURES

TECHNICAL REQUIREMENT :

- 1.Design standard: BS 5163.
- 2.Face to face: BS 5163.
- 3.Flanges standard: BS EN1092-2: 1997 PN16.
- 4.Test standard: BS EN12266-1 Rate B.

FEATURES :

- ◆ Double flange metal seated gate valve
- ◆ Size Range: DN50-DN2000
- ◆ Standard -ISO / BS / DIN / AWWA / API
- ◆ Tests Standard-BS EN 12266-1
- ◆ Body Ring-Bronze /SS420 /SS304 /SS316
- ◆ Disc Ring-Bronze /SS420 /SS304 /SS316
- ◆ Stem-Stainless Steel SS420 /SS431 /SS316
- ◆ Body-Ductile Iron / Cast Iron/Stainless Steel /WCB
- ◆ Disc-Ductile Iron /Cast Iron/Stainless Steel /WCB
- ◆ Fusion bonded epoxy coating-min 300 microns



RKS SMALL DIAMETER GATE VALVE
DN50 - DN300, PN10 / 16 /25



RKS METAL SEATED GATE VALVE
DN350 - DN600, PN10 / 16 /25



RKS LARGE DIAMETER METAL SEATED GATE VALVE
DN700 - DN2000, PN10 / 16 /25

APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HVAC



Food and drug



Water transport





I Business area: fluid control products, technology and environmental protection products.

II Advanced CNC machining centers, professional process cells, wide-range welding equipment, automatic assembly lines and coating.

III China's standard reference unit, to participate in the development of relevant valve industry standards.

IV We have set up a research and development center in Houston, Texas, in the United States.

V Product Standard: GB, German Standard, American Standard, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609.

VI Main production: butterfly valve, ball valve, gate valve, check valve, globe valves, pipe fittings, manual / pneumatic / electric actuator, valve parts.

Four factories



Why choose us



- 2 professional testing centers
- 28 senior professional researchers
- Independent research and development team



- 21 years of professional experience
- 100% high level ex-factory inspection
- 2 years quality assurance, repair and replacement

Our Factory



Exhibition Photos



Our Certificates



FAQ

Q: If I need quotation, what informations do we need?

A: Valves' materials, Temperature, Pressure, Medium, Appllication System.

Q: Can you provide actuators, what you have?

A: Pneumatic, Electric, Hydraulic, Solenoid Valves. RKSfluid actuators adopt USA technology. Which you need, just tell us.

Q: What's your productive capacity?

A: RKSfluid has four plants that can provide the products you need.

Q: Production lead time

A: Normal products have stock in 2~5 working days. Customized base on your need.

Q: MOQ

A: 1pc for all products.

Q: How about the quality assurance?

A: 100% quality test before delivery, 2 years warranty. Ensure your system working safety.

We got TUV, API, WRAS, CE, ISO certification.

Standard conform to DIN, ASME, BS EN, JIS, API, AWWA.

Q: How could you provide quality service to our customers?

A: RKSfluid own 20 years experiences and more than 70 R&D engineers provide technical support, model selection and installation guidance for you.

Ductile Iron Pn16 Dn100 Water Din 3352 F4 Resilient Seated Gate Flanged Valve