



Resilient seat butterfly valve



Resilient seat butterfly valve



Resilient seat butterfly valve

PN10/PN16, ANSI	125LB/150LB,5K/10K
-----------------	--------------------

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: DI+ Nylon

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange



Resilient seat butterfly valve



Double flange resilient seat butterfly valve



Short-neck butterfly valve for petroleum

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB, 5K/10K

Size:DN50-DN1000

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Flange

ANSI 125LB/150LB

Top Flange Standard:ISO5211

Size:2"-12"

Body: DI CI

Disc :Stainless Steel

Seat: EPDM, NBR, Viton

Connection:Wafer, Lug







BSEN 1092,	DIN 25	01, ANSI,	JIS,	AS2129
------------	--------	-----------	------	--------

Size:DN50~DN600

Body:Ductile Iron

Disc:Ductile Iron+PTFE

Seat: PTFE

Connection: Wafer, Lug, Flange

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: Ductile Iron+PTFE

Seat: PTFE

Connection: Wafer, Lug, Flange

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB, CF8, CF8M

Disc: CF8+PTFE, CF8M+PTFE

Seat: PTFE

Connection: Wafer, Lug







BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB, CF8, CF8M

Disc: CF8+PTFE, CF8M+PTFE

Seat: PTFE

Connection: Wafer, Lug

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: CF8, CF8M

Seat: PTFE

Connection: Wafer, Lug, Flange

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB

Disc: CF8 +PTFE, CF8 +PFA

Seat: PTFE

Connection: Wafer, Lug, Flange



Our Factory





The RKS fluid was founded in 1997. We are a production laboratory both for foundry and for mechanical processing, research and & development center and quality control center. Production facilities include numerical control work centers, professional processing cells, wide-spectrum welding equipment, automatic assembly and coating lines. We have created a team for design, research and & development. Our new test center as a public service platform

testing center in Liaoning province becomes the standard GB of the Chinese valve reference unit, to participate in the development of the related valve industry standards. In order to accelerate the expansion of business abroad and the integration of resources and to support the success of fluid sales of RKS in the United States, Germany and Russia. We have an American agent. Our product design standards include: GB, ISO, German and American standards, approved by TUV for CE and ADWO-2000, ISO9001, TS, API. Our products: manual, pneumatic and & ball valves, butterfly valves and electrically operated gate valves. Check valves, automatic control valves. Castings and fittings: valve bodies, hoods, disks, stems, gearbox, universal joints, flange adapters, saddle caps. After years of development, we continue to improve and seek innovation, adhering to "Proven technology, superior features and legendary value" as our product value philosophy. Customer satisfaction is our business goal!

Exhibition Photos

















